

# Huizhou Boxin Electronics Co., Ltd

Room 701, Building 5, Phase 1, Xin li kang le chuang Industrial Park, Renluoliu Road,  
Tel: 86-86-752-3558855 Fax: 86-752-3558820 http://www.boxinltd.com

## QUOTATION SHEET - HEADPHONES

Item	Picture	Description			SETS/CTN	CTN (L)	CTN (W)	CTN (H)	CBM/CTN	MOQ	Bluetooth version	Carton N.W. (KGS)	Carton G.W. (KGS)
		Model No.	Colour	Spec									
1		BX-200	black	Speaker Diameter:Ø40mm Speaker Sensitivity:108dB ± 3dB Impedance:32Ω Frequency Response:20Hz-20000Hz Microphone Sensitivity:-38dB ± 3dB Microphone Frequency:100-10000Hz Cable Length:1.8m Connector:3.5mm TRRS/USBA	20	47	37	40	0.0696	3K	/	8	9
2		BX-200	black	Speaker Diameter:Ø40mm Speaker Sensitivity:108dB ± 3dB Impedance:32Ω Frequency Response:20Hz-20000Hz Microphone Sensitivity:-38dB ± 3dB Microphone Frequency:100-10000Hz Cable Length:1.8m Connector:USB-A	20	47	37	40	0.0696	3K	/	8	9
3		BT-200	black	Bluetooth: 5.3 Speaker: Dia.40mm Speaker Sensitivity:108dB ± 3dB Impedance:32Ω Frequency Response:20Hz-20000Hz Microphone Sensitivity:-38dB ± 3dB Microphone Frequency:100-10000Hz Bluetooth distance: 10M Battery: 3.7V 350mAh Playing time: About 8H Charging time: About 2H Charging interface:USB-C Battery Type:Rechargeable lithium-ion battery	20	47	37	40	0.0696	3K	5.3	8	9
4		BT-003 JL	black	Bluetooth version: 5.2 Bluetooth Chip: JL-7018 Charging Port: Type C Speaker Frequency: 20-20KHz Rated Input Power: 20mW Max Input Power 30mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Bluetooth distance: > 10M Power dissipation: BLE Charging time: 1.5-2H Music Note: >28H Battery: 3.7V 300mAh Commnicate by telephone ENC select. Protein-like leather ear muffs Charging base attachable Three-dimensional arrangement	20	47	37	40	0.0696	3K	5.2	8	9
5		BT-003 QCC Teams+ENC	black	Bluetooth version: 5.2 Bluetooth Chip: QCC3040 Charging Port: Type C Speaker Frequency: 20-20KHz Rated Input Power: 20mW Max Input Power 30mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Bluetooth distance: > 10M Power dissipation: BLE Charging time: 1.5-2H Music Note: >28H Battery: 3.7V 300mAh Commnicate by telephone ENC select. Protein-like leather ear muffs Charging base attachable Three-dimensional arrangement	20	47	43	45	0.0909	3K	5.2	7	8

6		BT-006 JL	black	<p>Bluetooth version: 5.2  Bluetooth Chip: JL-7018  Charging Port: Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 20mW  Max Input Power 30mW  Speaker Diameter: Ø40mm  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Bluetooth distance: &gt; 10M  Power dissipation: BLE  Charging time: 1.5-2H  Music Note: &gt;28H  Battery: 3.7V 300mAh  Communicate by telephone ENC select.  Protein-like leather ear muffs  Charging base attachable  Three-dimensional arrangement</p>	20	47	43	45	0.0909	3K	5.4	7	8
7		BT-006 QCC Teams+ENC	black	<p>Bluetooth version: 5.2  Bluetooth Chip: QCC3040  Charging Port: Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 20mW  Max Input Power 30mW  Speaker Diameter: Ø40mm  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Bluetooth distance: &gt; 10M  Power dissipation: BLE  Charging time: 1.5-2H  Music Note: &gt;28H  Battery: 3.7V 300mAh  Communicate by telephone ENC select.  Protein-like leather ear muffs  Charging base attachable  Three-dimensional arrangement</p>	20	47	43	45	0.0909	3K	5.2	7	8
8		BX-393	black	<ol style="list-style-type: none"> <li>1. Headband type, stretchable</li> <li>2. Bluetooth 5.3 JL6983D</li> <li>3. Bluetooth transmitting distance: 10M</li> <li>4. Rechargeable battery: 17 hours working time.</li> <li>5.No ENC function.</li> <li>6. Compatible with Microsoft Windows Professional</li> <li>7.Net Weight: 90g/pc</li> <li>8. Packing: Boxin standard 4 off set color box, without window</li> </ol>	20	34	34	38	0.0439	5K	5.3	2.5	4
9		BT-001	black	<p>Charging Connection: Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 30mW  Speaker Diameter: Ø40 mm  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Bluetooth distance: &gt; 10M  Bluetooth Version: 5.3 JL-7018  Power dissipation: BLE  Charge time: 1.5-2H  Music Note: &gt;28H  Battery: 3.7V 300mAh  Communicate by telephone ENC select.</p>	20	50	50	38	0.0950	3K	5.3	6	7.2
10		BT-003	black	<p>Steel headband with Sand-blasting effect  Charging Port: Type C  <b>Bluetooth version: 5.3</b>  <b>Bluetooth Chip: JL7018</b>  Speaker Frequency: 20-20KHz  Rated Input Power: 20mW  Max Input Power 30mW  Speaker Diameter: Ø40mm  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Bluetooth distance: &gt; 10M  Power dissipation: BLE  Charging time: 1.5-2H  Music Note: &gt;28H  Battery: 3.7V 300mAh  Communicate by telephone ENC select.  Bluetooth Version, Metal Headband  Protein-like leather ear muffs  Charging base optional</p>	20	50	50	38	0.0950	3K	5.3	6	7.2









11		BT-003 Single	black	<p>Charging Port: Type C Steel headband with Sand-blasting effect Speaker Frequency: 20-20KHz Rated Input Power: 20mW Max Input Power 30mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Bluetooth distance: &gt; 10M Bluetooth version: 5.3 JL-7018 Power dissipation: BLE Charging time: 1.5-2H Music Note: &gt;28H Battery: 3.7V 300mAh Communicate by telephone ENC select. Bluetooth Version, Metal Headband Protein-like leather ear muffs Charging base attachable Three-dimensional arrangement</p>	20	50	50	38	0.0950	3K	5.3	6	7.2
12		BT-006	black	<p>Bluetooth version: 5.3 <b>Bluetooth Chip: JL-7018</b> Charging Port: Type C Speaker Frequency: 20-20KHz Rated Input Power: 20mW Max Input Power 30mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Bluetooth distance: &gt; 10M Power dissipation: BLE Charging time: 1.5-2H Music Note: &gt;28H Battery: 3.7V 300mAh Communicate by telephone ENC select. Protein-like leather ear muffs Charging base attachable Three-dimensional arrangement</p>	20	50	50	38	0.0950	1K or 3K	5.3	6	7.2
13		BT-006 Single		<p>Steel headband Charging Port: Type C Speaker Frequency: 20-20KHz Rated Input Power: 20mW Max Input Power 30mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Bluetooth distance: &gt; 10M Bluetooth version: 5.3 JL-7018 Power dissipation: BLE Charging time: 1.5-2H Music Note: &gt;28H Battery: 3.7V 300mAh Communicate by telephone ENC &amp; ANC select. Bluetooth Version, Metal Headband Protein-like leather ear muffs Charging base attachable Three-dimensional arrangement</p>	20	50	50	38	0.0950	3K	5.3	8	9.2
14		UC-001 Normal 3.5mm/USB	black	<p>Connection: USB Port Speaker Frequency: 20-20KHz Rated Input Power: 15 mW Max Input Power 20mW Speaker Diameter: Ø30mm Sound Level: 90dB ± 3dB at 1K Microphone Sensitivity: -6dB ± 3dB Microphone Frequency: 100-10000Hz Cord Length: 1.5m ± 5% Dimensions: 200mm x 50mm x 172mm Weight: 122g Basic Normal Version</p>	40	38.1	36.3	34.5	0.0477	3K	NA	8.8	9.7








15		UC-001 ENC	black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power:15mW  Max Input Power 20mW  Speaker Diameter: Ø30mm  Sound Level: 90dB ± 3dB at 1K  Microphone Sensitivity: -6dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Dimensions: 200mm x 50mm x 172mm  Weight: 122g  ENC Version</p>	40	38.1	36.3	34.5	0.0477	3K	NA	8.8	9.7
16		UC-001 Teams	black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 1 5 mW  Max Input Power 20mW  Speaker Diameter: Ø30mm  Sound Level: 90dB ± 3dB at 1K  Microphone Sensitivity: -6dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Dimensions: 200mm x 50mm x 172mm  Weight: 122g  Teams Version</p>	40	38.1	36.3	34.5	0.0477	3K	NA	8.8	9.7
17		UC-002 Normal USB	black	<p>Connection: USB Port  Speaker Frequency: 20-20KHz  Rated Input Power: 1 5 mW  Max Input Power 20mW  Speaker Diameter: Ø30mm  Sound Level: 90dB ± 3dB at 1K  Microphone Sensitivity: -6dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Dimensions: 200mm x 50mm x 172mm  Weight: 122g  Normal Version</p>	24	45.2	43.5	35	0.0688	3K	NA	6.57	8.07
18		UC-002 ENC	Black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 1 5 mW  Max Input Power 20mW  Speaker Diameter: Ø30mm  Sound Level: 90dB ± 3dB at 1K  Microphone Sensitivity: -6dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Dimensions: 200mm x 50mm x 172mm  Weight: 122g  ENC Version</p>	24	45.2	43.5	35	0.0688	3K	NA	6.57	8.07
19		UC-002 Teams	Black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 1 5 mW  Max Input Power 20mW  Speaker Diameter: Ø30mm  Sound Level: 90dB ± 3dB at 1K  Microphone Sensitivity: -6dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Dimensions: 200mm x 50mm x 172mm  Weight: 122g  Teams Version</p>	24	45.2	43.5	35	0.0688	3K	NA	6.57	8.07
20		UC-003 Teams	Black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 1 5 mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Impedance: 32Ω±15%  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.9m ± 5%  Busy Light, ENC.  Teams Version  Plug: Type C+Anti-lost Type C-USB</p>	44	58	37	45	0.0966	3K	NA	9.5	10.5

21		UC-003 Teams+ANC +ENC+Over Ear	Black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power: 1.5 mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Impedance: 32Ω±15%  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Busy Light, ENC.  Teams Version  With busy light  Plug: Type C+Anti-lost Type C-USB</p>	44	58	37	45	0.0966	3K	NA	9.5	10.5
22		UC-003 Normal USB	black	<p>Connection: USB Port  Speaker Frequency: 20-20KHz  Rated Input Power: 1.5 mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Impedance: 32Ω±15%  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.9m ± 5%  ENC.  Cable: 1.5M , RED TPE  Plug: USB</p>	44	58	37	45	0.0966	3K	NA	9.5	10.5
23		UC-003 Normal 3.5mm	black	<p>Connection: 3.5mm  Speaker Frequency: 20-20KHz  Rated Input Power:20mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Impedance: 32Ω±15%  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.9m ± 5%  Cable: 1.5M , RED TPE  Plug: 3.5mm</p>	44	58	37	45	0.0966	3K	NA	9.5	10.5
24		UC-003 Teams	black	<p>Connection: USB Port +Type C  Speaker Frequency: 20-20KHz  Rated Input Power:20mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.5m ± 5%  Busy Light, ENC.  Teams Version  With busy light</p>	44	58	37	45	0.0966	3K	NA	8	10.5
25		UC-003 Normal USB	black	<p>Connection: USB Port  Speaker Frequency: 20-20KHz  Rated Input Power:20mW  Max Input Power 20mW  Speaker Diameter: Ø40mm  Impedance: 32Ω±15%  Sound Level: 100dB ± 3dB at 1K  Microphone Sensitivity: -38dB ± 3dB  Microphone Frequency: 100-10000Hz  Cord Length: 1.9m ± 5%</p>	44	58	37	45	0.0975	3K	NA	8	9.5
26		BX-392 Normal 3.5mm/USB	black	<p>Speaker: 40mm Dynamic type  Impedance " 32Ohm  Sensitivity: 102dB±3dB  Frequency:20 ~ 20000Hz  Max Input Power:100mW  Cord length: 1.5m ± 5%  Normal version, USB port, Small Mic</p>	28	54	43	42	0.0975	3K	NA	11	12

27		BX-392 QD Connector	black	Speaker: 40mm Dynamic type Impedance * 32Ohm Sensitivity: 102dB±3dB Frequency:20 ~ 20000Hz Max Input Power:100mW Cord length: 1.5m ± 5% Normal version, USB port, Small Mic With QD Connector, BX-211 Voice Control	28	54	43	42	0.0975	3K	NA	11	12
28		BX-392 ENC	black	Speaker: 40mm Dynamic type Impedance * 32Ohm Sensitivity: 102dB±3dB Frequency:20 ~ 20000Hz Max Input Power:100mW Cord length: 1.5m ± 5% With ENC function 3.5mm/USB/USB+Type C Bigger Mic	28	54	43	42	0.0975	3K	NA	11	12
29		UC-006 Normal 3.5mm cable	black	Connection:3.5mm Speaker Frequency: 20-20KHz Rated Input Power:20mW Max Input Power 20mW Speaker Diameter: Ø40mm Impedance: 32Ω±15% Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Cord Length: 1.5m ± 5% Busy Light, ENC. Cable: 1.5M , RED TPE Plug: 3.5mm	40	20.5	18	40	0.0148	3K	NA	6.16	7.5
30		UC-006 Normal USB	black	Connection: USB Port Speaker Frequency: 20-20KHz Rated Input Power:20mW Speaker Diameter: Ø40mm Impedance: 32Ω±15% Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Cord Length: 1.5m ± 5% ENC Function Earmuff: Black Cable: 1.5M, Black TPE Plug: USB plug	40	20.5	18	40	0.0148	3K	NA	6.72	8.2
31		UC-006 Teams	black	Connection: USB Port +Type C Speaker Frequency: 20-20KHz Rated Input Power:20mW Max Input Power 20mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Teams Compatible Earmuff: Red Cable: 1.5M, Red TPE Plug: Type C+Anti-lost USB plug	40	20.5	18	40	0.0148	3K	NA	6.72	8.2
32		UC-006 Single Ear Teams	black	Connection: USB Port +Type C Speaker Frequency: 20-20KHz Rated Input Power:20mW Max Input Power 20mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Teams Compatible Earmuff: Red Cable: 1.5M, Red TPE Plug: Type C+Anti-lost USB plug	40	20.5	18	40	0.0148	3K	NA	5.1	6.1
33		UC-006 Single Ear Normal USB	black	Connection: USB Port Speaker Frequency: 20-20KHz Rated Input Power:20mW Max Input Power 20mW Speaker Diameter: Ø40mm Sound Level: 100dB ± 3dB at 1K Microphone Sensitivity: -38dB ± 3dB Microphone Frequency: 100-10000Hz Earmuff: Black Cable: 1.5M, Black TPE Plug: USB	40	20.5	18	40	0.0148	3K	NA	5.1	6.1

34		BX-211 Fixed cable	blue orange	Speaker: 40mm Dynamic type Impedance * 85dB Frequency:20 ~20000Hz Max Input Power:100mW Cord length: 1.5m ± 5% Fixed 3.5mm cable	20	52	38	36.5	0.0721	3K	NA	5	6.5
35		BX-211 Non Fixed cable	blue orange	Speaker: 40mm Dynamic type Impedance * 85dB Frequency:20 ~20000Hz Max Input Power:100mW Cord length: 1.5m ± 5% 3.5mm-3.5mm textile cable	20	52	38	36.5	0.0721	3K	NA	5	6.5
35		BX-211 Non-Fixed cable	blueorange	Speaker: 40mm Dynamic type Impedance * 85dB Frequency:20 ~20000Hz Max Input Power:100mW Cord length: 1.5m ± 5% 3.5mm cable to USB+Type C Textile cable	20	52	38	36.5	0.0721	3K	NA	5	6.5
36		BX-410	BlackGreen	1. Speaker: 40 mm 2. Impedance: 32 ohms 3. Sensitivity: 100dB±3dB 4. Frequency: 20 ~ 20000Hz 5. Max input power: 100mW 6. Cord length: 1.5m ± 5% 7.Headband cushion/Ear shell decoration ring: Green Pantone 390C Plastic color: Black 8. 3.5mm-3.5mm audio Jack, detachable 9. #350 Volumn Controller	20	52	38	36.5	0.0721	3K	NA	5	6.5
37		BX-410MIC	BlackBlue	1. Speaker: 40 mm 2. Impedance: 32 ohms 3. Sensitivity: 100dB±3dB 4. Frequency: 20 ~ 20000Hz 5. Max input power: 100mW 6. Cord length: 1.5m ± 5% 7.Headband cushion/Ear shell decoration ring: Blue Pantone 285C 8.Plastic color: Black 9. 3.5mm -USB to Type C plug, detachable 10. Volumn Control same as UC-003 11.Anti-lost USB-Type C plug	20	51	38	36	0.0698	3K	NA	5	6.5
38		BX-410MIC	BlackBlue	1. Speaker: 40 mm 2. Impedance: 32 ohms 3. Sensitivity: 100dB±3dB 4. Frequency: 20 ~ 20000Hz 5. Max input power: 100mW 6. Cord length: 1.5m ± 5% 7.Headband cushion/Ear shell decoration ring: Blue Pantone 285C 8.Plastic color: Black 9. 3.5mm -USB to Type C plug, detachable 10. Volumn Control same as UC-003 11.Anti-lost USB-Type C plug	20	51	38	36	0.0698	3K	NA	5	6.5
39		BX-K01	BlueBlack	Speaker: Dia.30mm Earmuff: Soft PVC, balck Cable: Fixed cable, textile cable+Sleeve Plug: Gun-shape silver color plug No Volumn Control	20	52	40.5	45.5	0.0958	3K	NA	5	6.3
40		BX-2800	BlackPurple	Speaker: Dia.30mm Earmuff: PVC, balck Cable: Fixed cable, textile cable+Sleeve Plug: Gun-shape silver color plug No Volumn Control	20	52	40.5	45.5	0.0958	3K	NA	5	6.3

41		GR03	Black	Speaker: Dia. 40mm Color: Black Earmuff: Black D43 Cable: Black TPE , 1.2M Mic: in line control, drill Volumn Control: Balck , XP50 Volumn Control Plug : 3.5MM	20	52	40.5	45.5	0.0958	3K	NA	5	6.3
42		BX-01	Black	Speaker: Dia. 40mm Color: Black Earmuff: Soft PVC Cable: Black TPE , 1.2M Volumn Control: Balck , 4877 Volumn Control Plug : 3.5MM	20	52	40.5	45.5	0.0958	3K	NA	4.5	5.7
43		BX-02	Black	Speaker: Dia. 40mm Color: Black Earmuff: Soft PVC Cable: Black TPE , 1.5M Volumn Control: Balck , 4877 Volumn Control Plug : 3.5MM	20	52	40.5	45.5	0.0958	3K	NA	4.5	5.7
44		BX-0514	Black	Speaker: Dia 40mm Dynamic type Impedance: 32ohms Sensitivity: 98dB+/- 4dB Frequency: 20-20KHz Max input power: 100mW Headband: Plastic Earmuff: Black PU, Over ear. Cable: 3.0 Black PVC 1.5M Plug: 3.5mm connector Mic: Omnidirectional noise-canceling microphone	40	52	39	35	0.0710	3K	NA	7	8
45		BX-1142	Black/Green	1. Speaker: 40 mm 2. Impedance: 32 ohms 3. Sensitivity: 100dB±3dB 4. Frequency: 20 ~ 20000Hz 5. Max input power: 100mW 6. Cord length: 1.5m ± 5% 7.Headband cushion Black/Ear shell decoration ring: Green 8.Plastic color: Black 9. Volumn Control same as UC-003 10. USB-Plug	30	51	38	36	0.0698	2K	NA	4.8	5.8
46		BX-1180	Black	1. Speaker: 40 mm 2. Impedance: 32 ohms, Dia.40mm 3. Sensitivity: 100dB±3dB 4. Frequency: 20 ~ 20000Hz 5. Max input power: 100mW 6. Cord length: 1.5m ± 5% 7.Color: Black 8. Earmuff: Black D43 9. Volumn Control: Balck , 4877 Volumn Control 10.Plug: 3.5MM	20	52	40.5	45.5	0.0958	3K	NA	5	6.3
47		BX-617	Black	Speaker: Dia. 40mm 32Ohm Color: Black Earmuff: Black D43 Cable: Black , TPE , 1.2M Mic: Inserted inside the ear shell Volumn Control: Balck , XP50 Volumn Control Plug : 3.5MM	20	47	37	40	0.0696	3K	NA	5	6.3
48		BX-630	Black	Speaker: Dia. 40mm 32Ohm Color: Black Earmuff: Black D43 Cable: Black , TPE , 1.2M Mic: 4887 on line Mic. Volumn Control: Balck , 4887 Volumn Control Plug : 3.5MM	20	47	37	40	0.0696	3K	NA	5	6.3

49		BX-640	Black	Speaker: Dia. 40mm 32Ohm Color: Black Earmuff: Black D43 Cable: Black , TPE , 1.2M Mic: 4887 on line Mic. Volumn Control: Balck , 4887 Volumn Control Plug : 3.5MM	20	47	37	40	0.0696	3K	NA	5	6.3
50		BX-40	Black	Speaker: Dia. 40mm 32Ohm Color: Black Earmuff: Black D43 Cable: Black , TPE , 1.2M Mic: 4887 on line Mic. Volumn Control: Balck , 4887 Volumn Control Plug : 3.5MM	20	47	37	40	0.0696	3K	NA	5	6.3
51		BX-821	Black	Volumn Control: XP50 , with Mic ON/Off Speaker: Dia. 40mm Cable: 3.0 Black TPE, 1.5M Plug : 3.5mm Mic: On line Mic, dual capacitor Earmuff: D43 Black	20	47	37	40	0.0696	3K	NA	5	6.3
52		BX-1138	Black	Speaker: Dia.40mm Cable: Fixed cable, 1.5M, Black TPE Plug : 3.5mm Volumn Control: #350 on line Volumn Control Earmuff: Black D43	20	47	37	40	0.0696	3K	NA	5	6.3
53		BX-390	Black	Headband: Bottom with black Cotton Earmuff: Black D43 Volumn Control: S043 Volumn Control, wiht MIC Mute cuntion, same as 100B board Speaker: Xunyin Dia.30mm Cable: 3.0 Black PVC 1.5M Plug: USB Mic: 6050 Inserted dual capacitor-38dB+/-3dB	8	43.6	26	25	0.0283	3K	NA	6	7.3
54		BX-760	Black	Earmuff: Frog soft leather Volumn Control: S043 Volumn Control, wiht MIC Mute cuntion, same as 100B board Speaker: Dia.40mm Cable: Fixed 3.5MM , 1.5M, Black Textile cable+Sleeve Plug : 3.5mm, Gun shape plug	8	43.6	26	25	0.0283	3K	NA	6	7.3
55		BX-NC108	Black	Speaker: Dia.40mm Headband: Black D43 Earmuff: Imitation Protein, Black Cable:3.5-3.5mm audio jack, detachable, Textile cable with Sleeve	20	47	37	40	0.0696	3K	NA	6	7.3

56			BX-210MIC	Black	Speaker: Dia.30mm Mic: Metal hose external microphone, ordinary microphone head, no microphone cotton Cable: PVC, 1.5M , 3.5 to USB cable #350 Volumn Control on line Earmuff: Frog Leather	40	52	39	32	0.0649	3K	NA	6.4	7.2
57			BX-216MIC	Black	Speaker: Dia.27mm Mic: Black Metal hose external microphone, Cable:3.0 fixed cable, 1.5M , black textile cable. #350 Volumn Control on line Earmuff: Black sponge	40	52	39	32	0.0649	3K	NA	5.8	6.8
58			BX-218MIC	Black	Speaker: Dia.30mm Mic: Black Metal hose external microphone, Cable:3.0 fixed cable, 1.5M , black textile cable. #350 Volumn Control on line Earmuff: Black sponge	40	56.6	28	35.5	0.0563	3K	NA	5.8	6.8
59			BX-696	Black	Speaker: Dia.50mm Headband: Inseted Stainless steel sheet, Leather: D43 Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Silver plated plug+ 6.3 Conversion line(Plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	7.6	8.9
60			BX-696	Black	Speaker: Dia.50mm Headband: Black Leather: D43 Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden plated plug+ 6.3 Conversion line(Plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	7.6	8.9
61			BX-695	Black	Speaker: Dia.50mm Headband: Stainless Steel rubber painted in Black Earmuff: Black Imitation Protein Cable: Plug cable, PU Spring cable, 3M Plug : 3.5mm Golden plated direct plug+3.5mm Golden plated Gun shape plug+ 6.3 Conversion line(with screw teeth) with Sleeve	20	55.5	46	37.5	0.0957	3K	NA	7.6	8.9

62		BX-324B	Black	Speaker: Dia.40mm Headband: Black, upper leather: Scratch resistant leather; Lower leather: D43 Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	7.5	8.7
63		BX-324B	Black	Speaker: Dia.40mm Headband: Black, Leather: D43 Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	7.5	8.7
64		BX-697	Black	Speaker: Dia.50mm Headband: Black, Upper Leather: D43; Lower Mesh cotton. Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	7.9	9.2
65		BX-699 Decoration ring E - plating	Black	Speaker: Dia.50mm Headband: Black, Upper Leather: D43; Lower Mesh cotton. Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	8.3	9.6
66		BX-699 Matt Black	Black	Speaker: Dia.50mm Headband: Black, Upper Leather: D43; Lower Mesh cotton. Earmuff: Black D43 Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (plastic head, no screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	8.3	9.6
67		BX-699 Rubber paint	Black	Speaker: Dia.50mm Headband: Black, Upper Leather: D43; Lower Mesh cotton. Earmuff: Imitation Protein Cable: Fixed cable, Black PVC Spring cable, 3M Plug : 3.5mm Golden-plated direct plug+6.3 conversion plug (with screw teeth)	20	55.5	46	37.5	0.0957	3K	NA	8.3	9.6
68		BT-699	Black	Speaker: Dia.50mm Headband: Black, Upper Leather: D43; Lower Mesh cotton. Earmuff: Imitation Protein Bluetooth: 5.3	20	55.5	46	37.5	0.0957	3K	NA	8	9

1. FOB Shenzhen for FCL shipment and EXW for LCL shipment
2. Standard brown box or color box package
3. Minimum order: 3K/5K.
4. Payment: 30% deposit and 70% before delivery by T/T.
5. Delivery time: 45-60 days after we get the deposit and all details confirmed if no stock.
6. Shipping port: Shenzhen