



Model: DXE350-Pro

35inch P-CAP Touch Shelf Edge LCD Display

Suitable for 900mm shelves



显示/LCD Spec	
尺寸/Size	35"LCD Panel
显示区域/Active area	877.82(H) ×45.72(V)mm
分辨率/Resolution	3840×200(RGB) 111PPI
亮度/Brightness	450cd/m ² (Typ.)
对比度/Contrast ratio	1000:1 (Typ.) (TM)
显示色彩/Display color	1.07B , 72% NTSC
背光源/Backlight	WLED
可视角度/Viewing angles	89/89/89/89 (Typ.)(CR≥10)
响应时间/Response time	8 (Typ.)(G to G) ms
液晶屏寿命/Lifespan	≥50000 hours
主板规格/Motherboard Spec	
芯片/CPU	Quad core ARM Cortex-A55
内存/RAM	2G DDR3(1 G/2G for optional)
内置存储/ROM	8G EMMC(8G/16G/32G/64GEMMC for optional可选)
外置存储/Memory extension	最大支持128G TF存储卡, TF Card extension with the highest support for 128GB
操作系统/System	Android 9.0
网络/Intetnet	支持2.4G无线WIFI接入, Support 2.4G WIFI connection
定时时钟/RTC real time clock	支持定时开关机功能, Support timing on / off function
接口/Interfaces	1xTF card slot/ 1x micro-USB(OTG)/ 1*Type-c(DC 12v)/ 1*USB
整机规格/Display Spec	
电压/Operating voltage	100-240V(50/60Hz)
功率/Power consumption	≤18W
外观尺寸/Outline	896.2*73.08*32.0mm
安装方式/Installation	挂墙式（支持壁挂板安装和葫芦孔两种挂墙方式）; Mounting bracket
外壳材质/material	金属钣金结构设计; Sheet Metal materials
净重/Net	≤2.5KG
表面处理/Surface treatment	黑色金属烤漆, Black metal paint
环境/Environment	
存储环境 /Storage	Temperature: -20℃~60℃ Humidity: 5%~95% Atmospheric Pressure: 86kPa~104kPa
工作环境 /Working Environment	Temperature: 0℃~50℃ Humidity: 10%~85% Atmospheric Pressure: 86KPa~104KPa
包装清单/Packing list	

显示器/Display	1pc
OTG数据线/Cable	1pc (OTG cable, micro USB to USB 2.0)
适配器/Adapeter	1pc (12V-2A)
壁挂支架/Bracket	1pc
认证/Certifications	
CE	YES (Issued by SGS)
RoHS	YES (Issued by SGS)
REACH	YES (Issued by SGS)
FCC ID	YES (Issued by SGS)
信息发布系统CMS Software (可选/Optional)	