

1.8" High Resolution LW61 Smart Watch [APP: OnWear Pro] Color:Black/Rose Gold/OEM

Mechanical

Water Resistance	3ATM
Display Size	1.78"
Screen Type	2.5D IPS-TFT
Screen Cover	Glass Cover
Middle Frame	Aluminum Alloy
Button	Aluminum Alloy,Sandblast,Oxidation
Bottom Shell Material	PC, Double Injection Mould
Wristband Material	Silicone
Buckle	Stainless Steel,Electroplate
Tongue clasp	Stainless Steel,Electroplate
Body Size (L x W x H) mm	45.5*37.9*10.7

Hardware

CPU	RTL8762DT
G SENSOR	stk8321,3axis G-sensor
PPG Heart rate sensor	HX3605
Screen	Capacitive full touch screen
Screen Resolution	320*390px
Flash	128MB
Bluetooth	BLE5.2

Power

Working Voltage	3.8V
Battery Life	7 Working Days, Standby 15 Days
Battery Capacity	330mAh
Type of Battery	Polymer lithium battery
Charging Method	Magnetic charging
Charging Time	<2.5 hour

APP OS

iOS	IOS 12.0+
Android	Android6.0+

Function

Language (General)	Chinese, English, Japanese, French, German, Spanish, Italian, Russian, Dutch, Greek, Czech, Portuguese (default: English)
	Support set on the watch
Basic Functions	12/24H Clock, Date Display
	Multi-dial,Online&DIY
	OTA upgrade

Daily activity monitoring	Heart rate (each 10min)
	Blood pressure(each 10min)
	Blood oxygen
	Breathing Training
	Steps, Calories,Distance(Auto)
	24H Sleep monitor(Auto)
Exercise Functions	Swimming,
	Yoga
	Mountaineering
	Free training
	Rowing Maching
	Elliptical Trainer
	Swimming
	Cricket
	Badminton
	Jump Rope
	Strength Training
	Football
	Basketball
	Outdoor Walk
	Outdoor cycle
	Indoor Run
Reminder	Incoming call
	SMS notification
	App push reminder
	Alarm
	Activity reminder
	Drink water reminder
	Women's Health
Other functions	Weather forecast
	110+ Sports
	Remote camera control
	A-GPS & Share
	Restore factory settings
	Stopwatch
	Restart
	Quick message reply(Android phone support)
	Timer
	Music control
	Scan QR code to download app
	Set the screen duration
	Firmware information
Gesture	Lift the wrist
	Lower the wrist
Environmental	
Working Temperature	-20°C to 50°C
Charge Temperature	0°C to 40°C
Working Humidity	10%-90%RH
Working Humidity	-20°C to 60°C
Storage Humidity	5%-90%RH