

SP-T Specification

Features:

Compact desktop size and High-speed printing
Convenient for handling
Different interfaces optional
Thermal and dot matrix printing method selectable
Easily connected to any kinds of instruments and meters

Specifications:

Printing method: thermal line/dot matrix
Printing speed: 15mm/s(direct thermal) 2.5lines/s 1.5lines/s (dot matrix)
Resolution: 8 dots/mm, 384 dots/line
Effective printing width: 32/48mm
Character set: IBM character set II, GB2312-80(Chinese)
Print font: ANK: 5 x 7, Chinese: 24 x 24, 16 x 16, 12 x 12
Character per line: 24/32/40
Paper type: thermal paper/plain paper
Paper width: 57.5mm; 0.5mm
Paper roll diameter:
Maximum: 40.0mm
Roll core inner diameter: 13mm(minutes)
MCBF(MCBF) Mean Cycles Between Failure: 5 million lines(direct thermal)/0.5 million lines(dot matrix)
Interface: RS-232, parallel
Paper supply method: semi-auto paper loading
Power supply: DC5V, 3A
Printer dimension(W x L x H): 156 x 101 x 40mm
Installation port size: N/A
Color: beige
Weight: 255g
Operating temperature: 0 to 50 degrees C
Operating humidity: 0 to 80%
Application: medical equipment, measuring equipment, security equipment, analyzing instrument and meter