



Model:	C20-H
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	AK3918 V300L
Resolution:	3MP(2304*1926P)
Sensor	1/2.7" Progressive Scan CMOS (SC2336)
Lens:	4MM
View angle:	80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression standard:	H.265/15FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	4pcs white LED + 4pcs Infrared LED
Network:	WIFI wireless transmission (support IEEE802.11b/g/n wireless protocol).
Network connection:	WIFI, AP Hotspot, RJ45 Network port
Night vision:	IR-CUT switch Automatic, about 10-15meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision auto , it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、DDNS、DHCP
Alarm:	Motion detection ,Voice Alarm and picture push
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A (Including power supply)
Package:	Color Box:20.2*18.2*13cm, 0.9kgs, CTN:67*42*56.5cm, 30pcs per ctn ,G.W.:23KGS
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH