


M12 X code female right angle molded cable, shielded/M12, X型母头弯头成型式连接线, 带屏蔽

Illustration/尺寸Product photo/产品图




Part number/产品料号

Pins/孔数	Code/型	Part number("X" is length millimetre mm)/产品料号("X"表示长度, 单位毫米mm)		
		PVC jacket/PVC外被	PUR jacket/PUR外被	
8pins/8孔	X code/X型	-10°C~+80°C	-40°C~+105°C	-40°C~+105°C
		12L01376-X	12L01377-X	12L01375-X

Pin assignment front view/针位分布前视图

X code 8pins
X型8孔



General data/常规数据

Pins Numbers/孔数	8pins/8孔
Rated voltage/额定电压	60V
Rated current(40°C)/额定电流	0.5A
Standards/标准	IEC 61076-2-101
Termination/焊接方式	solder and over-mold/焊接和成型
Degree of protection/防护等级	IP67, IP68, IP69K
Wire gauge(mm²)/线规(平方数)	0.14mm²
Wire gauge(AWG)/线号(平方数)	26AWG
Mechanical operation/插拔次数	>100 mating cycles/大于100次
Contact resistance/接触电阻	≤5mΩ
Insulation resistance/绝缘电阻	≥100MΩ
Connector body/胶芯	TPU
Pins/端子	Phosphorus copper with gold plated/磷铜镀金
Screw/螺丝	Brass with nickel plated/黄铜镀镍
Environmental compliance/环境符合标准	RoHs, Reach