



测试导线 Test Lead

J.70021*

4mm安全型公插转公插（可续插）

Test lead with stackable
4mm security male piug on
both ends



Rated voltage/current: CATIII 1000V/15A	0.75mm ²	025	050	100
Rated voltage/current: CATIII 1000V/19A	1.00mm ²	025	050	100
Rated voltage/current: CATIII 1000V/32A	2.50mm ²	025	050	100

J.70022*

4mm安全型公插转公插（可续插）

Test lead with stackable
4mm security male piug on
both ends



Rated voltage/current: CATIII 1000V/15A	0.75mm ²	025	050	100
Rated voltage/current: CATIII 1000V/19A	1.00mm ²	025	050	100
Rated voltage/current: CATIII 1000V/32A	2.50mm ²	025	050	100

J.70023*

4mm公插转公插（可续插）

Test lead with stackable
4mm male piug on both ends



Rated voltage/current: 30Vac-60Vdc/Max.15A	0.75mm ²	025	050	100
Rated voltage/current: 30Vac-60Vdc/Max.19A	1.00mm ²	025	050	100
Rated voltage/current: 30Vac-60Vdc/Max.32A	2.50mm ²	025	050	100

J.70024*

2mm公插转2mm母插

Test lead with 2mm male
piug and 2mm female plug
on both end



Rated voltage/current: 30Vac-60Vdc/Max.10A	0.50mm ²	025	050	100
--	---------------------	-----	-----	-----

J.70025*

4mm公插转4mm母插

Test lead with 4mm male
piug and 4mm female plug
on both ends



Rated voltage/current: 30Vac-60Vdc/Max.15A	0.75mm ²	025	050	100
Rated voltage/current: 30Vac-60Vdc/Max.19A	1.00mm ²	025	050	100
Rated voltage/current: 30Vac-60Vdc/Max.32A	2.50mm ²	025	050	100