

FIRST INDUSTRIAL DEVELOPMENT CO.,LIMITED

tel:0086 577 6256 8230 fax: 0086 577 6256 8230






Mobile: +86 133 8858 7626

Skype: daisyxiang123

E-mail: Daisy@firstcooler.com,info@firstcooler.com

Website: www.firstcooler.com

Absorption minibars

Picture					
Model	XC-28	XC-30	XC-32	XC-38	XC-50
Type of appliance	Freestanding or Built-in	Freestanding or Built-in	Freestanding or Built-in	Freestanding or Built-in	Freestanding or Built-in
Capacity	28L	30L	32L	38L	50L
Climate class	N	N	N	N	N
Inside temperature(solid door)	2°C to 8°C	2°C to 8°C	3°C to 8°C	5°C to 10°C	5°C to 10°C
Inside temperature(glass door)	10°C to 15°C	10°C to 15°C	12°C to 15°C	12°C to 15°C	12°C to 15°C
Voltage	220V/110V/12V	220V/110V/12V	220V/110V/12V	220V/110V/12V	220V/110V/12V
Power	60W	60W	60W	60W	60W
Power consumption	0.7 kw.h/24h	0.8 kw.h/24h	0.8 kw.h/24h	0.9 kw.h/24h	1.0 kw.h/24h
Cooling system	Absorption system	Absorption system	Absorption system	Absorption system	Absorption system
Protective class	I	I	I	I	I
Refrigerant	R717	R717	R717	R717	R717
Foaming agent	R141b	R141b	R141b	R141b	R141b
Thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Defrosting	Automatic	Automatic	Automatic	Automatic	Automatic
Exterior	Plastic coated steel sheet	Plastic coated steel sheet	Plastic coated steel sheet	Plastic coated steel sheet	Plastic coated steel sheet
Interior	highlight clad PS sheet	highlight clad PS sheet	highlight clad PS sheet	highlight clad PS sheet	highlight clad PS sheet
Internal light	Yes	Yes	Yes	Yes	Yes
Shelf	steel wire	steel wire	steel wire	steel wire	steel wire
Numbers of shelf	1	2	1	2	2
Door shelf	metal	metal	metal	metal	metal
Net/gross weight	12/13.50kg	13/15kg	14/15.50kg	15/17kg	16/18.50kg
Unit dimension	400*390*440mm	400*415*530mm	435*435*460mm	435*455*545mm	460*480*560mm
Packing dimension	425*435*500mm	435*455*590mm	475*475*520mm	495*475*600mm	485*525*650mm
Container load quantity	260/540/675 pcs	243/485/520 pcs	192/384/480 pcs	189/379/384 pcs	160/336/384 pcs
Certification	CE, RoHs	CE, RoHs	CE, RoHs	CE, RoHs	CE, RoHs
Options					
Wooden door	As your request	As your request	As your request	As your request	As your request
Glass door	As your request	As your request	As your request	As your request	As your request
Lock					