



- Authentic nature stone patterns
- Excellent wear resistant
- Easy maintenance
- Stain, slip and scratch resistance
- Excellent dimensional stability
- Recommend for: residential and commercial decoration.

Specification			
Thickness	2.0~5.0mm		
Wear Layer	0.1~0.7mm		
Size Available	18inx18in / 18inx24in / 12inx18in / 12inx24in (1in=25.4mm)		
Item	Standard	Unit	Result
Finish			UV
Abrasion	EN 660-2	mm ³	<2.0 Group T
Dimensional stability	EN 434 ASTM F2199	%	≤0.15%
Curling	EN 434	mm	≤2
Peel strength	EN 431	N/50mm	Residential >38 Commercial >45
Flexibility	EN435		No Crack
Castor chair suitable	EN 425		suitable
Color fasten to light	ISO105-B02	-	≥6
Color fasten to heat	ASTM F1514	-	No change
Stain resistance	EN 423	Class	0
Residual Indentation	EN433	-	≤0.1mm
Fire Behavior	EN ISO 9239-1		B _{FL} S ₁
VOC	CA Section 01350		Pass



BTL INDUSTRIES



BM-2001



BM-2006



BM-2009



BM-2010

BTL flooring

Focus on
LVT.Vinyl Roll.WPC Decking.Sport Flooring
www.btlfloor.com