

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial park, Sanjiao
Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85546950 **Fax** +86 0760-85546950
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



POS Cash Register Datasheet HS-B156

Function

- ◆ 15.6-inch LED Display protect waterproof dust-proof
- ◆ Capacitive touch screen
- ◆ With 32G SSD high-speed HDD
- ◆ With DDR 3 2G Memory
- ◆ Support USB, LAN, COM, PS/2, LPT, VGA interface
- ◆ With default trial windows7 system
- ◆ Can support single screen and Dual screen (Options)
- ◆ Support to Run any restaurant Software
- ◆ Run Fast, Stable, Durable
- ◆ High Quality ABS Strengthen Display shells
- ◆ New import LCD Display, the display color full, natural colors
- ◆ Taiwan 5-Wire resistive touch screen

Application



Supermarket



Hotel



Milk and tea shop



Color



Single screen



Dual Screen

Change to Dual Screen Add \$31

HSPOS TECHNOLOGY LIMITED
 5 floor, A1 building, Nanshui industrial park, Sanjiao
 Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
 Website: www.hsprinter.com
 Email: info@hsprinter.com



Parameters

Model No.	HS-B156
General	
CPU	Intel® Celeron® Processor J1800
Memory	DDRIII 1066/1333 2GB
HDD/SDD	32GSSD
LCD Panel	15.6" TFT LCD
Resolution	1024*768 (max)
Touch Panel	Capacitive touch screen
I/O Interface	
Audio	Realtek ALC662 5.1 channel HDA Codec, support MIC/Line-out Port
Ethernet	1*RJ-45(LAN) Realtek® RTL 8111C
Serial Port	1*COM on rear I/O
USB	6*USB 2.0 on rear I/O, 2*USB 2.0 on front
Keyboard&Mouse	1*PS/2 Keyboard & Mouse on rear I/O
LPT	1*LPT on rear I/O
DVI	N/A
HD	N/A
Display Interface	1*VGA on rear I/O
Environment & Price	
Power	AC 100-240V input 1U server dedicated mute power supply
Built-in Speaker	N/A
Operating Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Packing Size	430*530*320MM
Gross Weight	14KG