

B&T ZHANGZHOU (CABLE) CO.,LTD.

UL10368

Halogen Free Crosslinked Wire 无卤交联线

产品说明:

- 额定温度：105℃
- 额定电压：300V
- 参考标准：UL758,UL1581,CSA C22.2No.210.2
- 导体使用单支或绞合 30~10AWG 镀锡或裸铜
- XLPE 绝缘，符合 ROHS 环保标准
- 通过 UL 水平及 CSA FT2 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 105℃
- Rated voltage: 300V
- Reference standard: UL758,UL1581,CSA C22.2No.210.2
- Solid or stranded ,tinned or bare copper conductor 30~10AWG
- XLPE insulation ,comply with ROHS environmental standard
- Passes UL Horizontal and CSA FT2 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



印字 MARKING

AWM 10368 E330484 () AWG 105℃ 300V B&T CABLE c AWM I A FT2 105℃ 300V ()AWG

产品结构 CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 1min)
规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
30	1/0.254	0.25	0.25	0.75	361	2,000
	7/0.10	0.30	0.25	0.80	381	
28	1/0.32	0.32	0.27	0.85	227	2,000
	7/0.127	0.38	0.26	0.90	239	
	7/0.127OS-1*	0.38	0.26	0.90	239	
26	1/0.404	0.40	0.25	0.90	143	2,000
	7/0.16	0.48	0.26	1.00	150	
	7/0.16 OS-1*	0.48	0.26	1.00	150	
24	1/0.511	0.51	0.25	1.00	89.3	2,000
	7/0.20	0.60	0.25	1.10	94.2	
	7/0.20OS-1*	0.60	0.25	1.10	94.2	
22	1/0.643	0.64	0.25	1.15	56.4	2,000
	7/0.254	0.76	0.27	1.30	59.4	
	7/0.254 OS-1*	0.76	0.27	1.30	59.4	
20	1/0.813	0.81	0.27	1.35	35.2	2,000
	7/0.32	0.96	0.27	1.50	36.7	
18	1/1.024	1.02	0.27	1.55	22.2	2,000
	16/0.254	1.17	0.31	1.80	23.2	