

1 SATA 4/8CH H.265+ XVR Series KIT-412/812

Features :

- Support 4/8*1080N/5M-N/8M-N Video access;
- 4/8pcs Metal IR Bullet Camera;
- 4/8 rolls 18.3M BNC+DC Cable;
- 1/2pcs 12V 6A DC Adapter,1 to 5 Splitter;
- Support VGA 1080P, HDMI 1080P output;
- Mini 1U Case,1 SATA(Up to 8TB);
- H.265+/H.265/H.264 image decoding ;
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Max 16 times fast forward or fast reverse;
- Can connect with IP camera, IP dome, and Onvif supported;
- Support AHD/TVI/CVI/AVBS/IP 5-in-1,video signal automatic recognition;
- Support cloud service, network penetration and alarm information push function;
- Support remote access, DDNS to realize one-key remote monitoring;
- With UTC function, camera menu parameters can be adjusted via UTC function;
- Support mobile phone monitoring (iOS, Android);
- Support multiple browser access (IE, Chrome, Firefox,Safari);
- Support more than 20 languages and break the boundaries of national borders;
- Perfect protection circuit, unique triple watchdog function;
- Supporting WEB,VMS,MYEYE Platform, providing SDK Development;

Parameters :



Item	XVR-2154	XVR-2158
Processor	Hi3520DV200	Hi3520DV400
System	Embedded LINUX operating system	
Codec	H.265+ /H.265/H.264	
Multi Mode	4*5M-N;4*1080P(5 in 1) IP:16*1080P;16*960P Blend:2*1080P + 2*1080P(IP)	8*5M-N 6fps;8*4M-N 8fps (AHD) IP:16*1080P;8*5MP Blend:4*1080P(IP+AHD)
Playback	4*5M-N;4*1080P(5 in 1)	4*5M-N;8*4M-N
Compression	G.711A	
Record mode	Manual>Alarm>Dynamic Testing>Timing	
Storage mode	HDD Storage, Network Storage	
Backup	Network backup,USB HDD,USB record,SATA record	
Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:1080P)	
VGA output	1*VGA (MAX:1080P)	
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
Audio I/O	1/1	2/1
Alarm I/O	0/0	0/0
PTZ Control	RS485	RS485
USB Port	2*USB 2.0 port	2*USB 2.0 port
HDD	1*SATA interface (Up to 8TB)	
Temperature	-10 °C - + 55 °C	
Humidity	10% -90% RH	
Power supply	12V 2A DC	
Consumption	<10W (Without HDD)	
APP	XMEYE	
Weight	Around 1.0KG	Around 1.0KG
Dimension	250mm(L)* 210mm(W)* 45mm(H)	

Interface :



SHENZHEN JBE CCTV CO.,LTD

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,

Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China

Email:Sales@jbecctv.cn Tel:+86 0755 23037680

www.jbecctv.cn