






Add: Erkang Science Park, No. 1, Pingdong 6th Road, Nanping Science Park, Xiangzhou District, Zhuhai City, Guangdong China

Item No	Photos	Specs	Packing information
LC-SFL1A		<ol style="list-style-type: none"> Name: Solar 3-head wall lamp with remote control Lamp beads: 2835 * 230LED 8W Solar panel: High quality polycrystalline silicon, 5.5V 1.8W Battery specification: 1pc 3.7V 18650, total capacity 2000mAh Color temperature: 6000-7000K Waterproof grade: IP54 Lighting angle: adjustable from multiple angles <p>8 Working mode:</p> <ol style="list-style-type: none"> Induction mode (Full highlights when people come, and the light goes out 20-25s after people leave) Inductive+Slightly Bright Mode (Full highlights when people come, People walk slightly bright 10% brightness) Slightly bright no induction mode, slightly bright 30% <ol style="list-style-type: none"> Material: Polycrystalline silicon+ABS plastic+electronic components Sensing distance: Infrared sensing 3-5 meters Battery life: 11. Battery life: Fully charging for 6-8 hours, can be used for 7 days, can be used for 7 days Usage scenario: Family courtyard, villa, corridor, garden, swimming pool, road lighting 	<p>N.W: 0.492KG G.W: 0.596KG packing size: 21*14*11.5cm</p> <p>24pcs/CTN carton size: 58.5*43*36cm G.W: 15KG</p>
LC-SFL2A		<ol style="list-style-type: none"> Name: Solar 3-head wall lamp with remote control Lamp beads: 2835 * 280LED 8W Solar panel: High quality polycrystalline silicon, 5.5V 1.8W Battery specification: 2pcs 3.7V 18650, total capacity 2400mAh Color temperature: 6000-6500K Waterproof grade: IP54 Lighting angle: adjustable from multiple angles <p>8 Working mode:</p> <ol style="list-style-type: none"> Induction mode (Full highlights when people come, and the light goes out 20-25s after people leave) Inductive+Slightly Bright Mode (Full highlights when people come, People walk slightly bright 10% brightness) Slightly bright no induction mode, slightly bright 30% <ol style="list-style-type: none"> Material: Polycrystalline silicon+ABS plastic+electronic components Sensing distance: Infrared sensing 3-5 meters Battery life: Fully charging for 6-8 hours, can be used for 7 days Usage scenario: Family courtyard, villa, corridor, garden, swimming pool, road lighting 	<p>N.W: 0.425KG G.W: 0.545KG packing size: 19*12*12.4cm</p> <p>24pcs/CTN carton size: 46*39.5*38.5cm G.W: 13.8KG</p>
LC-100W		<ol style="list-style-type: none"> Lamp body material: Die-cast aluminum Solar panel: 5V/15W monocrystalline silicon panel Battery type: LiFePO4 battery 3.2V/12AH Working temperature: -35° to 60° Lamp beads: 7070*20pcs Color temperature: 6000K-6500K Lighting time in rainy weather: 3 days Control mode: lighting control+remote control/12h Color rendering index: Ra > 80 Lamp size: 225*195*55mm Solar panel size: 350*200mm 	<p>Light head 10pcs/CTN carton size: 42*29.5*25cm N.W: 8.6 KG G.W: 12.5 KG</p> <p>Solar Panel 20PCS/CTN Carton Size: 44.5*28.5*46cm N.W: 19.2 KG G.W: 23.5 KG</p>

Add: Erkang Science Park, No. 1, Pingdong 6th Road, Nanping Science Park, Xiangzhou District, Zhuhai City, Guangdong China

Item No	Photos	Specs	Packing information
LC-200W		<ol style="list-style-type: none"> 1. Lamp body material: Die-cast aluminum 2. Solar panel: 5V/25W monocrystalline silicon panel 3. Battery type:LiFePO4 battery 3.2V/18AH 4. Working temperature: -35° to 60° 5. Lamp beads: 7070*30pcs 6. Color temperature: 6000K-6500K 7. Lighting time in rainy weather: 5 days 8. Control mode: lighting control+remote control/12h 9. Color rendering index: Ra > 80 10. Lamp size: 305*265*55mm 11. Solar panel size: 350*400mm 	<p>Light head 8pcs/CTN carton size:55.5*25.5*33cm N.W:10c KG G.W:13.5 KG</p> <p>Solar Panel 10PCS/CTN Carton Size:37.5*28.5*42.5cm N.W:13.7 KG G.W:17 KG</p>
LC-300W		<ol style="list-style-type: none"> 1. Lamp body material: Die-cast aluminum 2. Solar panel: 5V/35W monocrystalline silicon panel 3. Battery type:LiFePO4 battery 3.2V/25AH 4. Working temperature: -35° to 60° 5. Lamp beads: 7070*48pcs 6. Color temperature: 6000K-6500K 7. Lighting time in rainy weather: 5 days 8. Control mode: lighting control+remote control/12h 9. Color rendering index: Ra > 80 10. Lamp size: 365*320*55mm 11. Solar panel size: 350*600mm 	<p>Light head 6pcs/CTN carton size:37*33.5*38.5cm N.W:11.8 KG G.W:15.8 KG</p> <p>Solar Panel 10PCS/CTN Carton Size:36.5*28.5*62.5cm N.W:18.8 KG G.W:23.2 KG</p>