

MODEL		GSP 24-10
RATED VOLTAGE (V)		- DC24
RATED CURRENT (A)		10
MAX.PV MODULES POWER(KWp)		0.24
PV ARRAY INPUT CONTROLLER PATH		1
MAX.CURRENT EACH PV ARRAY (A)		10
STORAGE BATTERY OVER DISCHARGE PROTECTIVE VALUE (V)		43.2
STORAGE BATTERY OVER DISCHARGE RECOVERY (V)		49
STORAGE BATTERY OVER CHARGE PROTECTIVE VALUE (V)		58
LOAD OVER VOLTAGE PROTECTIVE VALUE (V)		65
LOAD OVER VOLTAGE RECOVERY VALUE		60
UN-LOAD CURRENT(mA)		< 100
VOLTAGE	PV ARRAY AND STORAGE BATTERY (V)	0.3
DROP	STORAGE BATTERY AND LOAD (V)	0.1
TEMPERATURE COMPENSATION FACTOR (mV/C)		0~5(TUNABLE)
OPERATING TEMPERATURE (°C)		- 20~ + 50
WORKING ALTITUDE (m)		≤5000 (DECREASED THE CAPACITY AS GB/3859.2 WHEN ALTITUDE HIGHER THAN 1000MTS)
PROTECTIVE DEGREE		IP20
WALL MOUNTING TYPE SIZE (W×H×D mm)		482×132×270 (WITH HAND SHANK)