

4G LTE TDD Solar IP Camera IP4-THS-400

Features:

- ◆ 4G LTE TDD Solar IP Camera.
- ◆ 2.0 Megapixel 1080P H.265+.
- ◆ 2pcs Array IR +4pcs White Light LED.
- ◆ TF Card Max 128G,Two Way Audio.
- ◆ Built-in 3MP 4mm Fixed Lens.
- ◆ 5.5W Solar Panel (5.5V/1000mA).
- ◆ 4pcs 18650 Battery 10400mAh.
- ◆ IP66 Weatherproof Standard.
- ◆ Response Time:0.6S,;Detection angle:110°.
- ◆ Photographic distances:0-10Meters.



Key Feature:

- 1/2.8" SONY CMOS sensor.
- 1920*1080P@20fps.
- 2pcs Array IR +4pcs White Light LED.
- Outdoor Bullet Metal IP Camera.
- White Metal body with strong bracket.
- Built-in 2pcs efficient antennas 4G.
- 3MP/5MP 4mm HD Fixed Lens.
- Support IR cut filter with auto switch.
- 4G wireless remote monitoring,support for all 4G SIM card.
- Support Three-Stream technology.
- Two-way Audio(with Microphone and Speaker).
- Support Micro SD/SDHC/SDXC card, the maximum up to128G.
- Support SMART IR, P2P and cross-browser access.
- Mobile APP Name: CamhiPro.
- CMS:HiP2P for PC.
- 5.5W Solar Panel (5.5V/1000mA),4pcs 18650 Battery 10400mAh.
- Response Time:0.6S,;Detection angle:110°.
- Photographic distances:0-10Meters.

4G Frequency Range:

- Europe: LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8
- USA: LTEFDD: B2/B4/B5/B7/B8/B12/B17 LTE TDD: B38/B40/B41 WCDMA: B2/B4/B5/B8
- China: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41 WCDMA: B1/B5/B8

Product Advantages:

- Offer 3-Years Product Warranties.
- Logistics convenient.
- CCC/CE/FCC Certified.
- Strict product quality control.
- Efficiently working with 4G NVR.
- Lower price.

Product Applications:

This is the best product of safety field. It and hard disk video recorders,cable,power supply,display,etc. Constitute a complete security system. Its application is more extensive. Such as homes,factories,highways,office building,garden,community, or a large public places, etc.

Model No.	IP4-THS-400
Image Sensor	Hi3516EV200+IMX307
Resolution	1080P=1920*1080
Illumination	Color 0.001 Lux@F1.2(AGC on), B&W 0.00 Lux@F1.2(IR on)
Lens Mount	Built-in 3MP 4mm Fixed Lens
IRLED	Built-in 2pcs Array IR LED + 4pcs White Light LED
IR Distance	30M (Night Vision)
System	PAL / NTSC
Resolution	Main Stream: 1920*1080@20FPS; Second Stream:1920*960@25FPS; Third Stream: 640*480,320*240@25FPS;
JPEG Video Bitrate	Q720P:640*352;QQ720P:320*176;Special For Mobile Phone View
Frame	2.0MP and below 20fps(50HZ)
Video Processing	H.265+ video coding, support dual stream, AVI format; code stream 32~6144kpbs adjustable
	Support 3DNR,Support Digital WDR,Support JPEG Snapshot
Image Setting	Brightness, contrast, saturation, exposure, up and down inversion, left and right mirror adjustable
Audio	Built-in Microphone and Speaker
Network Protocol	TCP/IP,HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, IPv6, IPv4
Storage	TF Card (Max 128G)
Motion Detection	4 independent detection areas can be set (sensitivity 1-100 can be set)
Wake Up Mode	PIR,APP
Action with alarm	Send the alarm picture to the designated mailbox; Alarm upload pictures and videos to FTP server
Sim Card	Support 2G/3G/4G
Type of network	FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
Operating Frequency	LTE B1/B3/B8/B38/B39/B40/B41
	WCDMA 2100/900MHz、TD-SCDMA B34/B39
	TD-SCDMA B34/B39
	GSM/GPRS/EDGE: 900/ 1800MHz
Speed	FDD-LTE/TDD-LTE:UP 50M /Down 150Mbps
	HSPA+:UP 5.76M /Down 21Mbps
	TD-SCDMA:UP 2.2Mbps /Down 2.8Mbps
USIM/SIM	Micro SIM Card
WIFI Protocol	802.11b/g/n(Max 72Mbps Speed)

SHENZHEN JBE CCTV CO.,LTD

APP	CamhiPro
CMS	HiP2P
Function	Configure by WEB, OSD(on screen display),real-time video transmission, motion detection and IO alarm linkage ,center prompt and picture pop-up after IO alarm; support remote surveillance client software;support mobile monitoring(iPhone, Android).
Solar Panel	5.5W Solar Panel (5.5V/1000mA)
Battery	4pcs 18650 Battery 10400mAh
Photographic distance	0-10Meters
Shooting Angle	85°
Induction range	0-10Meters
Detection angle	110°
S/N Ratio	>=50dB
ES	1/50 - 1/10,000S
White Balance	Auto Tracking White Balance
Gamma Ratio	>=0.45
Working Temp.	Outdoor: -40C to +60C
Humidity	0 to 95% RH (non-condensing)
Consumption	450mA
Voltage Input	Power 12V DC 2A
Single Package	1.5kgs/23*13*13mm
8pcs/Carton	72*46.5*50CM 13.5KGS

SHENZHEN JBE CCTV CO.,LTD

www.jbecctv.cn

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,
Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China
Email:Sales@jbecctv.cn Tel:+86 0755 23037680