

型号	腔型	开边给料口尺寸(mm)	紧边给料口尺寸(mm)	最小排料口尺寸(mm)	处理能力(th)	最大装机功率(kw)
Model	Cavity type	Open side feed opening size	Tight edge feed opening size	Min outlet size	Processing capacity	Maximum installed
P200	C2(粗)	235	190	19	65-250	160
	M(中)	171	120	16		
	F1(细)	150	95	13		
	F2(超细)	116	70	8		
-P300	C1(超粗)	265	230	25	85-440	22d
	C2(粗)	240	210	20		
	M(中)	190	150	15		
	F1(细)	145	105	11		
	F2(超细)	120	80	8		
HP400	C1(超粗)	360	290	30	135-625	315
	C2(粗]	310	250	25		
	M(中)	260	196	20		
	F1(细)	182	110	13		
	F2(超细)	135	90	10		
HP500	C1(超粗)	370	330	38	200-790	400
	C2(粗)	320	290	28		
	M(中)	245	210	22		
	F1(细)	180	130	13		
	F2(超细)	150	95	10		
HP800	C1(超粗)	450	352	38	265-1200	630
	C2(粗)	373	298	32 25		
	M(中)	340	375			
	F1(细)	280	230	16		
	F2(超细)	235	150	10		