
PRODUCT DESCRIPTION:

- ★Rated temperature:80℃
- ★Rated voltage:300V
- ★According to:UL Subject758,UL1581,C22.2
- ★Solid or stranded,tinned or bare copper conductor 32--16AWG
- ★PVC insulation
- ★Passes UL VW-1&CSA FT1 vertical flame test
- ★Uniform insulation thickness of wire to ensure easy stripping and cutting
- ★For general purpose internal wiring of appliance

Conductor		Finished product			Maximum Resistance at 20℃
AWG	NO.of Cond	Insulation Thick.	Outside Thick.	Packing	
	mm	mm	mm	m/r	Ω/mm
30	7/0.1	0.41	1.10	610	354.33
28	7/0.127	0.41	1.20	610	223.75
26	7/0.16	0.41	1.30	610	139.76
24	11/0.16	0.41	1.40	610	88.36
22	17/0.16	0.41	1.60	610	60.16
20	21/0.178	0.41	1.80	610	38.58
18	34/0.178	0.41	2.10	610	22.98
16	26/0.254	0.41	2.40	610	15.06
28	1/0.320	0.41	1.15	610	227.39
26	1/0.404	0.41	1.25	610	142.79
24	1/0.511	0.41	1.35	610	89.39
22	1/0.643	0.41	1.50	610	54.30
20	1/0.813	0.41	1.65	610	33.90
18	1/1.024	0.41	1.85	610	21.40

博尔特（漳州）电缆有限公司