



惠州市联兴彩印包装有限公司

LX Packaging (Huizhou) Co., Ltd.

21#, Longhu Rd., LongQiao Ave. LongXi, Boluo, HuiZhou City, GuangDong 516121

TEL: +86 752-6876 596 FAX: +86 752 6876 591 WEB: www.lxpac.com

Product Technical Specification

Product Description: Aluminum Retort Pouch

Material Structure: PET12/AL7/NY15/RCPP70

Size(mm): -

Physical Characteristics:

Item	Unit	Standard	Test Method
Sealing Strength	N/15mm	≥ 40	QB/T2358
Bone Strength	N/15mm	≥ 1.8	GB8808
		≥ 2.5	
		≥ 3.5	
Coefficient of Friction		-	GB/T10006
Oxygen Transmission Ratio	cm ³ /m ² , 24hrs	≤ 0.5	ASTD3985-96
Water Vapour Transmission	g/m ² , 24hrs	≤ 0.5	ASTMF1249-91
Tensile Strength	n/15mm	≥ 40.0	GB/T1040.3-2006
		≥ 40.0	
Elongation	%	≥ 25.0	GB/T1040.3-2006
		≥ 25.0	
Residual of Solvent	mg/m ²	≤ 5.0	GB/T 10004-2008