




0722-S Series



0722 - S C Q ## M

Series Switch Mounting Terminal Panel Thickness Switch Type



► Specification	► Inlet	► Rocker Switch
Power Rating	16A 250V AC Europe 20A 250V AC North America	10A 250V AC
Electric Strength	AC 2,000V for 1 Minute	AC 1,500V for 1 Minute
Contact Resistance	30MΩ Max.	20MΩ Max.
Insulation Resistance	100MΩ Min. at 500V DC	100MΩ Min. at 500V DC
Operating Temperature	+80°C	+ 125°C
Materials	Thermoplastic UL Flammability 94V-0 & Copper Alloy	Thermoplastic UL Flammability 94V-2 & Copper Alloy
Mounting	C : Screw-on P : Snap-in	Double Pole (On / Off Switch)
Terminal	Q : Q.D / Solder Tab, 4.8 X 0.8 S : Solder Tab, 3.5 X 0.8 W : Q.D Tab, 6.3 X 0.8 P : PCB Pin	Q.D Tab, 4.8 X 0.8 Solder Tab, 3.5 X 0.8 Q.D Tab, 6.3 X 0.8
Panel Thickness	Snap-in Panel Thickness : 1.0 / 1.2 / 1.5	Switch Type M : Illuminated

Unit : mm

