

# 4G LTE Mobile WIFI (MIFI)

Model: L410A



<b>SoC</b>	ASR1803S CAT4 / ASR5803W
<b>Dimension</b>	98*66*15mm
<b>Bands</b>	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)
<b>Form factor</b>	MIFI
<b>Battery</b>	Li-ion Battery 2100mAh Working time: 5-6 hrs, Standby time: around 300 hrs (Depend on network)
<b>Wi-Fi</b>	802.11 b/g/n, WIFI speed up to 72Mbps, max 10 users connection
<b>Memory</b>	256Mb RAM
<b>Data Rates</b>	LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL
	USB                      USB2.0, Type C
	SIM                        3FF (eSIM / VSIM optional)
	LED                        Battery/WIFI/Signal
<b>Hardware</b>	Antenna                  Build-in FPC type
	Power Voltage            USB DC 5V
	Button                    Reset(Pinhole), Power
	Update                    FOTA & Local update
<b>Software</b>	Support OS                Compatible with Windows / MACOS / Linux / Android
	Others                     IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics, WIFI Security
<b>Operation Temperature</b>	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80%
	Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%

- ✓ LTE Cat4 ASR1803S/L Cost effective Solution
- ✓ eSIM/VSIM support optional