



深圳市卡联科技股份有限公司
SHENZHEN CARDLAN TECHNOLOGY CO., LTD

Address: Liantang Industrial Park, Kangzheng Road, Danzhotou, Nanwan
Sub-district Office, Longgang District, Shenzhen City, China
Email: alvin@cardlangroup.com Tel: 0086-15707972752

CL-A0618B Smart Bus Validator Specification



Shenzhen Cardlan Technology

Contents

CL-A0618 SMART BUS VALIDATOR SPECIFICATION.....	
1. PRODUCT APPEARANCE.....	
2. INTERFACE EXPLANATION.....	
3. APPLICATION ENVIRONMENT.....	
4. FUNCTION FEATURES.....	
5. TECHNICAL PARAMETERS.....	



1. Product appearance



2. Interface explanation

- USB-HOST port

This USB-HOST interface is a USB host device that supports U disk and USB keyboard for upgrading configuration software and downloading related device files. The maximum output is 5V/500mA.

- USB-OTG port
- USB-DEBUG port
- PSAM card slot



CL-A0618 has 4 PSAM slot, support

encryption with CPU card payment

- SIM card slot

CL-0618 has 1 SIM card slot, mainly used for 4G wireless communication, insert SIM card , realize remote data communication.

3. Application environment

CL-A0618 smart bus validator can support RFID card, with GPS positioning module, support GPRS, WIFI wireless communication etc. Can be used for electronic payment or card validation in following field:

- Public transport fare collection
- Scenic spots/amusement park card payment
- Balance inquiry
- Employee shuttle bus card validation
- Safety school bus system

4. Functional features

- Support wireless communication, remote connect to server management software to realize real time time-revision, black-list downloading and data collection etc.
- Support data real time uploading or USB local data collection
- Support live voice prompts, supports 15 kinds of voice prompts: such as "student card", "employee card"
- Support consumption details and statistics query, according to card No., time, operator No., etc.



5. Technical parameter

Name :	Smart Bus Validator
Operating System :	Android5.1
CPU :	Quad-core cortex-a9 main frequency 1.4GHz、integrated GPU Mali-400 MP4
RAM	DDR3 1G (default)
Memory :	eMMC 8G (default) 、Max support 64G TF card
Memory Function	
Data Capacity :	more than 2 million detailed data for console storage, extensible
Blacklist :	Two hundred million, extensible, more with TF card
Working Environment	
Working Temperature:	-25℃~65℃
Storage Temperature:	-40℃~85℃
Working Humidity:	0-90% (non-condensing)
Physical Parameter	
Dimension:	240x170x74.7mm
Housing material:	Engineering plastics
LCD Display	
Display :	5 inch LCD display, 800*480
Indicator light :	Red and green
Camera	
Scanning:	Wide angel/QR /customized
Distance:	0CM -15CM
Voice Prompt	
Sound Prompt :	Buzzer、Single channel loudspeaker



Voice Prompt :	16KHz,16bit single channel voice prompt
Power Supply Specification	
Audio	8Ω ,2W
Working Voltage :	DC 8V-50V
RFID Function	
Support Type :	Can read and write ISO14443 TYPE A\B Electronic tag
Reading Distance :	0~50mm
Working Frequency :	13.56Mhz
Card Capacity :	5,000,000 pcs
Card Type :	Mifare 1 card, CPU card, UnionPay IC card
Interface	
Communication Interface :	USB-HOST、 USB-OTG、 RS485 or TTL-232
Reserved interface:	HDMI
Printing Function	
Printing module :	Support external POS58printer (need 5pinaviation plug turn DB9 cable)
Width of receipt: :	58mm
Positioning Function	
Position way :	GPS, Beidou positioning (Optional)
Working Mode	
Working Mode :	Stand-alone or connect to server
Power Consumption	
Power Consumption:	≤10 W
Communication Function	
Wireless Communication	GPRS,3G,4G optional
WIFI	Support 802.11n/b/g standard,150Mbps,2.4Ghz
Warning Function	
Warning Function	Warning when card balance is insufficient or data memory is full



深圳市卡联科技股份有限公司

SHENZHEN CARDLAN TECHNOLOGY CO.,LTD

Address:Liantang Industrial Park, Kangzheng Road, Danzhutou, Nanwan
Sub-district Office, Longgang District, Shenzhen City, China
Email: alvin@cardlangroup.com Tel: 0086-15707972752

Data Collection Function	
Collection mode	2G、3G、4G and USB collection WIF and Bluetooth optional Ethernet Port- Optional : 1x Built-in 10/100-base-T Ethernet

----END----