

Brand	Innolux	Model P/N	N156HCN-E5A
Diagonal Size	15.6"	Panel Type	a-Si TFT-LCD, LCM
Resolution	1920(RGB)×1080, FHD 141PPI	Pixel Format	RGB Vertical Stripe
Active Area	344.16(W)×193.59(H) mm	Bezel Opening	-
Outline Size	350.66(W)×205.24(H) ×5(D) mm	Surface	Antiglare, Hard coating (3H)
Brightness	250 cd/m ² (Typ.)	Contrast Ratio	1000:1 (Typ.) (TM)
Viewing Angle	89/89/89/89 (Typ.)(CR≥10) ?	Display Mode	AAS, Normally Black, Transmissive ?
Best View on	Symmetry	Response Time	11/9 (Typ.)(Tr/Td)
Display Colors	262K 45% NTSC	Lamp Type	WLED , 15K hours , With LED Driver
Frequency	60Hz ?	Touch Screen	On-Cell Touch, I ² C
Shape Style	Slim (PCBA Bent, T≤3.0mm)	Application	
Signal Interface	eDP (2 Lanes) , eDP1.2 , 40 pins Connector		
Input Voltage	3.3V (Typ.)		
Environment	Operating Temp.: 0 ~ 50 °C ; Storage Temp.: -20 ~ 60 °C		

[★ Add to Favorites](#)
[🔊 Book Stock Alert](#)
[+ Add to Compare](#)
[🇺🇸 North American Sales](#)
[🇯🇵 日本販売](#)