



Kiosk embedded printer HCC-EU804

Features

- 80mm thermal receipt printer
- Anti-blocking paper and anti-pull paper function
- Compatible with ESC/POS command
- Long printing life
- Indicator light function

Specification

Print	Printing Method	Thermal Line
	Printing Speed	150 mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ASCII, GB18030(Chinese), BIG5
	Print Font	ASCII:12×24;8×16; 9×17
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5±0.5mm(with SP-MF1), 82±0.5mm
	Paper Thickness	0.06~0.08mm
	Paper Roll Diameter	More than: 80.0mm
Reliability	MCBF	1 million lines
Barcode		1D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 2D: PDF417, QRCODE, DATAMATRIX
Bitmap print command		Support printing bitmaps with different density and downloaded graphics.
Characters print command		Support the double width and height printing of ANK characters,self-defined characters and Chinese; characters lines spacing can be adjusted
Emulation		ESC/POS,CPCL(option)
Driver		Windows 98 / ME / 2000 / NT / XP / 2003 Server/Vista/Win7/Win8
Interface		USB
Paper Supply Method		Manual paper loading
Power Supply (Adapter)		DC24V±10%, 2A
Power Plug interface		VH3.96-4P
TPH		100KM

Auto cutter	Type	Guillotine
	Life	1,000,000
	Cutting Method	Partial Cut/ Full cut
Physical	HCC-EU804U	251.5*120*109.3mm
	HCC-EU804MF(with SP-MF1)	274.3*120*109.3mm
	Operating Temp/Humidity	0~50℃ /10%~80%
	Storage Temp/Humidity	20~60℃ /10%~90%

Picture

