


成品图

注:带▲为需管控尺寸

REV.	ECN NO.	DATE



SPECIFICATION NOTES:

1. Electrical:

- 1.1 Voltage rating: 125 VAC RMS
- 1.2 Current rating: 1.5 A
- 1.3 Contact resistance: 50 milliohms max
- 1.4 Insulation resistance: 1000 megaohms min @ 500 VDC
- 1.5 Dielectric strength: 1000 VAC RMS 50Hz, 1MIN.

2. Mechanical:

- 2.1 Retention strength: 50N MIN FOR 60S±5S
- 2.2 Operating life: 750 CYCLES MIN
- 2.3 Insertion force: 30N MAX.

3. Material & finish:

- 3.1 Housing: PC UL94V-2 clean
- 3.2 Contact: copper alloy plated with gold
- 3.3 Shield: Brass plated with Nickel
- 3.4 Operating temperature: -40 °C to +80 °C.

A : stranded wire

H : solid wire

ORDER INFORMATION:

S7907 C F 88 X X X A-X

special recognition code

F: flat cable

terminal shape code

2
4
6
8
number of contact

0:semi-finished product without terminal
7:gold plating01u"
8:gold plating03u"
9:gold plating06u"
A:gold plating15u"
B:gold plating30u"
C:gold plating50u"

未注公差 (mm)		东莞市华翔电子有限公司				TITEL 品名	PLUG	
x	±0.30					PART NO. 料号	S7907CF88XXXA-I01	
.xx	±0.15	核 准	审 查	绘 图	HU	DATE 日期	2020/08/24	
.xxx	±0.05					SCALE 比例	1:1	VIEW 视角
	±2.0					REV 版本	A.0	