

Model				9K	12K	18K	24K
Nameplate Parameter	Rated Capacity	Cooling	W	2640（900-3000）	3600(1200-4000)	5300（1300-5300）	7000
	Rated Power Consumption	Cooling	W	870（300-1600）	1300(400-1600)	1760（235-1900）	2300
	Rated Running Current	Cooling	A	4.0（1.5-8.5）	6.41(1.8-8.5)	8.5（1.1-8.9）	10.5
	Max. Input Power		W	1600	1600	1900	2650
	Max. Input Current		A	8.5	8.5	9	14.5
	EER Cooling		W/W	3.1	2.8	17	3.04
	Power supply source		V/Ph/Hz	220V~/50Hz	220V~/50Hz	220V-1-50HZ	220～V-1-50Hz
	Refrigerant			R32	R32	R32	R32
	Air Flow Volume		m3/h	600	550	850	1300
	Noise level - Indoor Unit		dB（A）	43	42	47	49
	Noise level - Outdoor Unit		dB（A）	51	51	52	55
	Indoor unit weight（Net）		Kg	8.5	8.5	11	13.5
	Outdoor unit weight（Net）		Kg	21	21	23	38.5
Indoor unit configuration	Net Dimension (WxDxH)		mm	750×285×200	750×285×200	900×310×225	1082×330×233
	Packing Dimension (WxDxH)		mm	820*347*277	820×347×277	970×382×302	1155×397×312
Outdoor unit configuration	Compressor			SANYO	SANYO	SANYO	GMCC
	Net Dimension (WxDxH)		mm	1.3P-705×279×530	1.3P-705×279×530	1.3P-709×285×535	2P-825×655×310
	Packing Dimension (WxDxH)		mm	825×345×595	825×345×595	810×330×570	945×725×435
Container Loading 40HC			Sets	255	255	225	155