

Daisy Xiang Sales Manager

FIRST INDUSTRIAL DEVELOPMENT CO.,LIMITED

tel:0086 577 6256 8230 fax: 0086 577 6256 8230

mobile: 86 158 2544 3655(whatsapp,wechat)/ 86 133 8858 7626

web: www.firsth2o.com

email: daisy@firsth2o.com,info@firsth2o.com

skype:Daisyxiang123

Stainless Steel Drinking Water Fountains



GHE5G

GHE5G-1

Model:	GHE5G		GHE5G-1
Rated Voltage:	220-240V/ 50H/110-120V /60Hz/127V/60Hz		
Rated Power:	Heating:	N/A	500W
	Cooling:	110W	110W
Compressor Type:	Hermetic, with overload protector, R134a		
Cold Water Tank Capacity:	3.5 L (drawing SUS 304)		3.5 L (drawing SUS 304)
Heating Capacity:	N/A		2L
Cooling Capacity:	8.0L/Hr at 8-12°C (25-37°F)against ambient temperature 25°C (77°F)		
Heating Capacity:	N/A		5L/Hr at 90-95°C (281-297°F)against ambient temperature 25°C (77°F)
Faucet:	1		2
Pressure Device:	Include decompression valve		Include decompression valve
N.W	17 kg (37.5lb)		18kg(39.6lb)
G.W	18.5kg (40.8lb)		19.5kg(42.9lb)
Machine Diemension:	305 (D) x 315(W) x 980(H)mm		
	12.0" (D) x12.4"(W) x 38.6"(H)		
Packaging Diemension:	320(D) x 330(W) x 1080(H)mm		
	12.6" (D) x13"(W) x 42.5"(H)		
MOQ:	1*20FCL		1*20FCL
Required Water Pressure:	0.07-0.5Mpa		
Required Water Source:	Water Bottle Loading		
Loading Quantity:	1*20FCL	252 units	252 units
	1*40GP	518 units	518 units

- Unique stainless steel water loading water dispenser, durable, Robust, corrosion resistant and reliable.
- Hot+cold water or cold+warm water are both available.
- Compressor cooling.