

UL2570

Jacketed Cable 护套电线

产品说明

- 额定温度: 80℃
- 额定电压: 1000V
- 参考标准: UL758, UL1581, CSA C22.2No.210.2
- 导体使用单支或绞合镀锡或裸铜
- PVC 绝缘, 符合ROHS 环保标准
- PVC 护套, 符合ROHS 环保标准
- 通过UL VW-1、CSA FT1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮

PRODUCT DESCRIPTION

- Rated temperature: 80℃
- Rated voltage: 1000V
- Reference standard: UL758, UL1581, CSA C22.2No.210.2
- Solid or stranded, tinned or bare copper conductor
- PVC insulation, comply with ROHS environmental standard
- PVC jacket, comply with ROHS environmental standard
- Passes UL VW-1, CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting



印字 MARKING

AWM 2570 E330484 VW-1 80℃ 1000V XXAWG B&T CABLE
c AWM I A FT1 80℃ 1000V XXAWG -LF-

产品结构 CABLE CONSTRUCTION

导体				绝缘		护套		最大导体电阻 MAX.COND. RESISTANCE
CONDUCTOR				INSULATION		JACKET		
规格 AWG	构造CONSTR- UCTION	外径	芯数	绝缘厚度 INSULATION THICKNESS	外径	护套厚度	外径	
	(No./mm)	DIA.(mm)	(No)	(mm)	O.D. (mm)	JACKET THICKNESS (mm)	O.D. (mm)	
28	7/0.127	0.38	2	0.80	2.0	0.8	5.60	223.75
			3				6.00	
			4				6.50	
			5				7.20	
			6				7.60	
			7				7.60	
26	7/0.16	0.48	2	0.80	2.05	0.8	5.70	139.76
			3				6.10	
			4				6.60	
			5				7.20	
			6				7.90	
			7				7.90	
24	11/0.16	0.61	2	0.80	2.2	0.8	6.00	88.36
			3				6.40	
			4				7.00	
			5				7.60	
			6				8.20	
			7				8.20	
			2				6.40	

22	17/0.16	0.76	3	0.80	2. 4	0.8	6.90	60.16
			4				7.40	
			5				8.20	
			6				8.80	
			7				8.80	
20	26/0.16	0.94	2	0.80	2. 55	0.8	6.70	38.58
			3				7.20	
			4				7.80	
			5				8.60	
			6				9.40	
18	41/0.16	1.2	7	0.80	2. 75	0.8	9.40	22.98
			2				7.10	
			3				7.60	
			4				8.40	
			5				9.20	
			6				10.00	
			7				10.00	

