



FENICE POWER

Line interactive ups

Model	BK650
Capacity	650VA/360W
Input Voltage	220/230/240Vac
Input Voltage Range	140-300VAC
Input Frequency Range	50 Hz/60Hz(Auto sensing)
Output Voltage	220/230/240Vac
AC Voltage Regulation	±10% (Bat Mode)
Frequency Range	50Hz/60Hz ± 1Hz (Bat Mode)
Transfer time	Typical 2--6ms
Waveform (Bat Mode)	Simulated Sine wave
Battery	Lead-acid battery
Battery Type & Number	12V/7Ah*1
Floating Charging Voltage	13.7VDC
Case	Plastic
Charging ability	4-6 hours recover to 90% capacity
Full protection	Overload, discharge, over charge, short circuit, over / under voltage protection
Line mode	Green lighting
Battery mode	Yellow flashing
Fault	Red lighting
Battery mode	Sounding every 10 seconds
Low battery	Sounding every second
Overload	Sounding every 0.5 seconds
Alarm	Sounding every 2 seconds
Fault	Continuously sounding
Dimension,D*W*H(mm)	297*101*142
Net Weight (kgs)	4.2
Humidity	0-90% Relative Humidity 0-40 °C (Non-condensing)
Noisy Level	Less than 40dB

*All Specifications subject to change without notice

Features

- Compact size and ergonomic design: it can be placed on a desk top or other convenient
- Perfect protection for overload ,short circuit ,over-voltage ,low-voltage and over-heatin
- Boost and buck AVR for voltage stabilization
- Excellent microprocessor control optimizes reliability
- Off mode charging and cold start function
- Line mode, Battery mode and fault alarm
- Auto restart while AC is recovering
- Echo friendly and user friendly

