

Model / Picture	Discription
GY496TG250W	Light power: 250w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 7kg, Carton: 57.5x30x21cm/1 pc,
GY496TG500W	Light power: 500w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 14kg, Carton: 41x58x26cm/1 pc,
GY496TG750W	Light power: 750w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 23kg, Carton: 58x58x26cm/1 pc,
GY496TG1000W	Light power: 1000w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 30kg, Carton: 74x58x26cm/1 pc,
GY496TG1500W	Light power: 1500w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 45kg, Carton: 112x28x63cm/1 pc,
GY496TG1500W	Light power: 1500w, LPW: 150lm/w, LED: 3030, Input Voltage: AC100-277V, Driver: Moso, Beam angle: 30/60/90/120 degrees, IP66, PF: 0.97, Ra>70, Working temperature: -40 to 40 degrees, NW: 45kg, Carton: 112x28x63cm/1 pc,