

Shandong Tianyu construction Machinery CO., LTD

Brand	Model	basic	lifting capacity	dimension of cage	work speed	container	FOB price	section dimension
		height		(3m×1.3m×2.3m)				
Tianyu	SC200/200	50m	2000kg*2	double cages	33m/min	40'HQ*1		650×650×1508mm

remark:1, there is no any commission in the price,they are net price. 2,every 40'HQ can contain 67 units mast section.

parameters	主要性能参数	单位				SC200×200
	额定载重量 Payload capacity	kg				2×2000
	额定安装载重量 Erection load capacity	kg				2×1000
	吊杆额定载重量 Lifting device capacity	kg				250
	吊笼内部面积(长×宽) Cage platform dimension	m				3×1.3
	最大架设高度 Maximum lifting heights	m				150
	提升速度 Speed	m/min				33
	电机功率 Rated output	kw				2×3×11
	防护等级 Port.D	/				IP55
	额定电流 current	A				2×2×23.5
	供电熔断器电流 Power supply fuses	A				2×63



防坠安全器 Safety device	m/s				1.2
外笼重量 Enclosure weight	kg				1480
吊笼重量 Cage weight	kg				2×1200
标准节重量 Mast section weight	kg				167
标准节长度 Mast section length	mm				1508
减速比 RATIO i=1:16					









