



2" mobile thermal label printer HCC-T2PL-B

Features

- 2 inch mobile receipt thermal label printer
- Portable device suited for outdoor usage
- Black mark paper location sensor
- Low battery indicator(7.4V,2000mAh)
- Equipped with lithium battery for 4-8 hours continuous work
- Various interfaces communication and interface capacities
- Bluetooth with high communication speed
- Easy paper loading
- High printing speed, up to 80mm/s
- Support Android, IOS, Linux.

Specification

Printing Method	Thermal Line
Resolution	8 dots/mm, 384 dots/line
Effective Printing Width	48mm
Printing Speed	100mm/s (Receipt paper); 80mm/s (Label paper)
Character Set	ASCII, GB18030(Chinese), BIG5
Print Font	ANK: 12x24, 9x24 Chinese: 24x24
Self-defined Character	Yes
Barcodes	EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25
Driver	Windows XP/Windows Vista/Windows 7/IOS/Linux
Graphic	Support bitmap downloading
Paper End Sensor	Yes
Overheating Protection	Yes
Black Mark Location	Yes
Auto Sleeping	Yes
Interface	Bluetooth+USB
Battery	DC7.4V,1.5A rechargeable Li-ion battery
Charger	DC9V/2A
Printer head life	50km
Paper Type	Thermal paper / thermal label paper
Paper Width	57.5± 0.5mm
Paper Thickness	0.06 to 0.08mm
Paper Roll Diameter	40mm (Max.)
Paper Supply Method	Drop-in Easy loading

Paper Cutting Method	Manual
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C/10%-90%
Dimension (L x W x H)	105 x 75 x37mm
Weight	235g
Standard Accessory	1* User Manual, 1* CD Driver, 1* Power Adapter 1*USB Data Cable 1*Test Paper Rolls 1*battery
Package info	One set size:210*125*65mm One set weight:0.6kg

Picture

