

Daisy Xiang Sales Manager

FIRST INDUSTRIAL DEVELOPMENT CO.,LIMITED

tel:0086 577 6256 8230 fax: 0086 577 6256 8230

mobile: 86 158 2544 3655(whatsapp,wechat)/ 86 133 8858 7626

web: www.firsth2o.com

email: daisy@firsth2o.com,info@firsth2o.com

skype:Daisyxiang123

Stainless Steel Drinking Water Fountains

  600E	Model:	YLR-600E(Hot+Cold)	YL-600E(Cold only)
	Rated Voltage:	220-240V/ 50H/110-120V /60Hz/127V/60Hz	
	Rated Power:	Heating:	1000W
		Cooling:	120W (Force cooling system)
	Compressor Type:	Hermetic, with overload protector, R134a	
	Cold Water Tank Capacity:	5.0L (1.3Gallon) Built-in Evaporator	
	Heating Capacity:	Inner hot 10L/Hr (2.6Gallon) at 90-95 °C (277-293 °F)	N/A
	Cooling Capacity:	8L/H(default),up to maximum 40L/H output for option.	Cold:8L/H,Hot:10L/H
	Machine Materials:	SS304 stainless steel,Thickness:0.8mm,rim inside pressed	
	Cooling way	Fan Cooling or condensing cooling for optional	
	Filter System:	Available for selection	
	Faucet:	1decompression faucets & 1muzzles	1decompression faucets & 1muzzles
	Pressure Device:	Include decompression valve	Include decompression valve
	N.W	30 kgs	28 kgs
	G.W	32 kgs	30 kgs
	Machine Diemension:	280 (D) x 360 (W) x 1230(H)mm	280 (D) x 360 (W) x 1230(H)mm
		12.0" (D) x12.4" (W) x 48" (H)	12.0" (D) x12.4" (W) x 48" (H)
	Packaging Diemension:	320 (D) x 410 (W) x 1110 (H)mm	320 (D) x 410 (W) x 1110 (H)mm
		12.6" (D) x16.1" (W) x 44" (H)	12.6" (D) x16.1" (W) x 44" (H)
	MOQ:	1*20FCL	1*20FCL
	Required Water Pressure:	0.07-0.5Mpa	
	Required Water Source:	City Water	
	Loading Quantity:	1*20FCL	196 units
		1*40GP	406 units
• Simplistic heavy duty stainless steel finish • Dispenser jet with mechanical Push-button bubbler • Sturdy glass/bottle-filler up • Direct chill cooling system • Low maintenance • Integral 1 1/4" draining tap complete with mains waste access port and flexi waste pipe • Filters system available for option • Optional electronic controlled leak detector system(shuts off electricity and water supply) • Optional wall and floor-fix bracket kit • Optional waste pump • Optional blanking plug set for use when the swan bottle filler tap is not required. • Removable back panel for ease of waste connection • Install & waste kit included • Integrated ventilation • Floor-standing drinking water fountains • Economy model			