



Shenzhen Ployer Electronics Co., Ltd.

Address: 6F, Building 8, Rundongsheng Industrial Area, Longzhu Community, Xixiang Street, Bao'an District, Shenzhen, 518000, China.

Model: P1012	Specifications			
Octa-Core & 10.1-inch 4G-LTE   Standard Accessories: Power Adapter, USB Cable, User Manual, Screen Protective Film and Gift Box. (Protective Film is already well attached to the screen) Casing: Metal (Private Tooling) Device size: 243 x 162 x 8.4 mm	Display	10.1-inch IPS screen, FHD 1200*1920 Capacitive 10 Points Multi-touch (2.5D G + FF Touch Panel) Full Lamination Process Supports Pressure Pen (Touch IC: Goodix 9110P)	Wi-Fi	Built-in Dual-Bands Wi-Fi Module IEEE 802.11 a/b/g/n/ac (2.4G + 5G)
			Bluetooth	Supported (BT 4.2)
	CPU	Octa-core (8 cores), MediaTek MT8788, Cortex-A73 + Cortex-A53; Speed: up to 2.0GHz [Unisoc (Spreadtrum) T618 CPU optional Speed: 2.0GHz]	GPS	Supported
			HDMI	N/A
			Phone Call	Supported
	GPU	ARM Mali-G72 MP3	IM Card	Supports 2*Nano-SIM Card
	RAM	4GB (3GB/4GB/6GB optional)	2G/3G/4G Network	Built-in 4G: 4G-LTE TDD: B38/39/40/41 4G-LTE FDD: B1/2/3/5/7/8/17/20 3G WCDMA: B1/2/5/8 3G TD-SCDMA: B34/39 2G GSM: B2/3/5/8
	Memory	64GB (32GB/64GB/128GB optional)		
	System	Google Android 11 OS		
	Camera	Front: 5MP (2MP optional) Rear: 8MP+Flash (5MP/13MP optional)	TF Card	Supports Micro-SD Card, 32GB max
			Speaker/MIC	Built-in BOX Speaker*2, Microphone*2
	Battery	7500 mAh	Charging	Type-C, 5V==2A (Quick Charge Optional)
			Data Transfer	USB Type-C (Data + Earphone + Charging)
	I / O Ports	1 x Type-C (Data + Earphone + Charging) 1 x Hybrid SIM tray (3-choose-2), supports dual Nano-SIM card + Micro-SD expansion Optional: Docking for Keyboard	Others	Built-in: FM, G-sensor, Motor (Vibration), Proximity sensor, Light sensor, Hall IC. Optional: Gyroscope, Compass

