

SMD LED C37 G45



C37



G45-E27



G45-E14

Code	Model	Cap	W	Volt	LM	CRI	Beam Angle(°)	Lifetime	H(mm)	Diam.(mm)
io-401001	C37-4	E14/E27/B22	4W	220-240V	320	80	160	20000h	103	37
io-401002	C37-6	E14/E27/B22	6W	220-240V	470	80	160	20000h	103	37
io-401003	G45-4	E14/E27/B22	4W	220-240V	320	80	160	20000h	80	45
io-401004	G45-6	E14/E27/B22	6W	220-240V	470	80	160	20000h	80	45

SMD LED A60



A60/A65



A60S

Code	Model	Cap	W	Volt	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401005	A60	E27/B22	7W	220-240V	470	80	20000h	110	60
io-401006	A60	E27/B22	9W	220-240V	810	80	20000h	110	60
io-401007	A65	E27/B22	12W	220-240V	1050	80	20000h	125	65
io-401008	A60S	E27/B22	13W	85-265V	1400	80	20000h	110	60

Bulb Dimmable SMD LED



C37D



G45D



A60D

Code	Model	Cap	W	Volt	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401009	C37D-5.5W	E14	5.5W	220-240V	470	80	25000h	103	37
io-401010	G45D-5.5W	E14/E27	5.5W	220-240V	470	80	25000h	80	45
io-401011	A60D-10W	E27	10W	220-240V	806	80	25000h	110	60

SMD LED G115 T30



G115



T30

Code	Model	Cap	W	Volt	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401012	G115-16	E27	16W	220-240V	1400	80	25000h	154	115
io-401013	G115-18	E27	18W	220-240V	1600	80	25000h	154	115
io-401014	T30-1.5	E14	1.5W	220-240V	100	80	25000h	76	30
io-401015	T30-2	E14	2W	100-240V	150	80	25000h	76	30