

IR Dome Camera Series

FEATURES:

- Unique IR Dome Case Design
- 3.6mm Fixed Lens With Premium Quality (6mm & 8mm Lens Optional)
- 3D Free Rotation Housing Design
- Regular or Day/Night model both available



SPECIFICATIONS

Model	UC-RD011	UC-RD111	UC-RD211	UC-RD311	UC-RD511	UC-RD811
Image Sensor	1/3"Sharp CCD and DSP	1/3"Sony Super HAD CCD and DSP				1/3"Sony Super HAD CCD w/Nextchip DSP
Signal System	PAL/NTSC					
Effective Pixels	PAL: 512(H)X582(V) NTSC:512(H)X492(V)	PAL: 512(H)X582(V) NTSC:512(H)X492(V)		PAL: 752(H)X582(V) NTSC:762(H)X494(V)	Pal: 811(H)X508(V) NTSC:795(H)X596(V)	
Horizontal Resolution	420TVL	420TVL	450TVL	480TVL	520TVL	540TVL
Video Output	Composite 1.0Vp-p at 75ohm					
S/N Ratio:	≥48dB(AGC OFF)					
Mini Illumination	0.8LUX/F1.2	0.5LUX/F1.2		0.5LUX/F1.2	0.5LUX/F1.2	0.5LUX/F1.2
Sync. System	Internal					
Electroinc Speed	1/50(60)-1/100,000sec (PAL/NTSC)					
White Balance	Auto					
Backlight compensation	Auto					
Exposure Mode	EE/AI					
Lens	3.6mm Fixed Lens (6mm, 8mm Lens Optional)					
Power	DC 12V					