

Model			YSTAB-12CRN1	YSTAB-18CRN1	YSTAB-22CRN1	YSTAB-28CRN1	YSTAB-31CRN1
Power supply		Ph-V-Hz	230V,1Ph,60Hz	220-230V,1Ph,60Hz	230V,1Ph,60Hz	220-230V,1Ph,60Hz	230V,1Ph,60Hz
Cooling(T1)	Capacity	Btu/h	12000	18000	22000	28000	31400
	Input	W	976	1488	1781	2258	2614
	Rated current	A	4.33	6.6	7.9	10.01	11.6
	EER	W/W	3.6	3.55	3.62	3.63	3.52
Cooling(T3)	Capacity	Btu/h	10600	15900	18200	23200	26800
	Input	W	1191	1849	2128	2713	3122
	Rated current	A	5.18	8.2	9.42	12.1	13.85
	EER	W/W	2.608	2.52	2.507	2.506	2.516
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	GMCC	GMCC	HIGHLY
Indoor unit	Dimension(W*D*H)	mm	965x215x319	1080x226x335	1080x226x335	1259x282x362	1350x272x365
	Packing (W*D*H)	mm	1045x305x410	1155x415x315	1155x415x320	1340x450x380	1475x460x380
	Net/Gross weight	Kg	11.5/15	14.9/18.7	14.1/17.8	22.8/28.5	21.3/27.3
Outdoor noise level		dB(A)	55	56.5	56	58.5	61
Outdoor unit	Dimension(W*D*H)	mm	770x300x555	845x363x702	946x410x810	946x410x810	946x410x810
	Packing (W*D*H)	mm	900x348x625	965x395x765	1090x500x885	1090x500x875	1090x500x885
	Net/Gross weight	Kg	30.1/33	44.7/48	60.9/65.5	64.9/69.4	68.4/73
Refrigerant type		Kg	R410A/0.85	R410A/1.1	R410A/2.2	R410A/2.55	R410A/2.6
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control	Remote Control
Operation temperature		℃	17~30	17~30	17~30	17~30	17~30
Room temperature	Indoor(cooling/ heating)	℃	17~32//	17~32//	17~32//	17~32/0~30	17~32//
	Outdoor(cooling/heating)	℃	18~54//	18~54//	18~52//	18~54/-7~24	18~52//
Application area (Cooling Standard)		m2	16~23	24~35	29~43	37~55	42~61
Qty'per 20' /40' /40'HQ			86/180/208	60/126/142	44/92/108	36/76/88	36/73/90