

UL1429

■产品说明

- 额定温度:80℃
- 额定电压:150V
- 参考标准:UL758,UL1581,CSA C22.2No.210.2
- 导体使用单支或绞合 32~16AWG 镀锡或裸铜
- XLPVC 绝缘, 符合ROHS 环保标准
- 通过UL VW-1、CSA FT1 阻燃测试
- 绝缘厚度均匀、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

■PRODUCT DESCRIPTION

- Rated temperature: 80℃
- Rated voltage: 150V
- Reference standard: UL758,UL1581,CSA C22.2No.210.2
- Solid or stranded ,tinned or bare copper conductor 32~16AWG
- XLPVC insulation ,comply with ROHS environmental standard
- Passes UL VW-1,CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



■印字 MARKING

AWM 1429 E330484 VW-1 80℃ 150V **AWG B&T CABLE c AWM I A FT1 80℃ 150V **AWG -LF-

■产品结构 CABLE CONSTRUCTION

编号	导体 CONDUCTOR			绝缘 INSULATION	完成外径Overall diameter(mm)		最大导体电阻 MAX. COND. RESIS TANCE Ω /km, (20℃, DC)	参考 重量 Approx. weight (g/m)	参考 包装 Standard packing (m)
	规格 SIZE	构造 CONSTRUCTIO N (No. /mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	标准Standard	公差 Tolerance			
14293207XX	32	7/0.08	0.24	0.31	0.90	±0.1	556	1.21	盘装
142932070SXX	32	7/0.08 OS=1	0.24	0.31	0.90	±0.1		1.07	
14293201XX	32	1/0.20	0.2	0.31	0.85	±0.1			
14293007XX	30	7/0.10	0.30	0.31	0.95	±0.1	381	1.47	盘装
142930070SXX	30	7/0.10 OS=1	0.30	0.31	0.95	±0.1		1.32	
14293001XX	30	1/0.254	0.254	0.31	0.90	±0.1			
14292807XX	28	7/0.127	0.38	0.31	1.00	±0.1	239	1.84	盘装
14292807XX	28	7/0.127 OS=1	0.38	0.31	1.00	±0.1		1.65	
14292801XX	28	1/0.32	0.32	0.31	0.95	±0.1		2.48	
14292607XX	26	7/0.16	0.48	0.31	1.10	±0.1	150	2.21	610
14292601XX	26	1/0.40	0.40	0.31	1.05	±0.1			
14292411XX	24	11/0.16	0.61	0.31	1.25	±0.1	94.2	3.5	610
14292407XX	24	7/0.20	0.60	0.31	1.25	±0.1		3.05	
142924070SXX	24	7/0.20 OS=1	0.60	0.31	1.25	±0.1			
14292401XX	24	1/0.51	0.51	0.31	1.15	±0.1	60.16	4.88	610
14292217XX	22	17/0.16	0.76	0.31	1.40	±0.1		4.43	
14292207XX	22	7/0.254	0.76	0.31	1.40	±0.1			
142922070SXX	22	7/0.254 OS=1	0.76	0.31	1.40	±0.1			
14292201XX	22	1/0.64	0.64	0.31	1.30	±0.1	38.58	6.83	610
14292026XX	20	26/0.16	0.94	0.31	1.60	±0.1		6.47	
14292010XX	20	10/0.254	0.94	0.31	1.60	±0.1			
14292007XX	20	7/0.32	0.94	0.31	1.60	±0.1			
14292001XX	20	1/0.813	0.813	0.31	1.50	±0.1			
14291841XX	18	41/0.16	1.20	0.31	1.85	±0.1		10.24	

14291816XX	18	16/0.254	1.20	0.31	1.85	±0.1	22.98	10.14	610
14291801XX	18	1/1.024	1.024	0.31	1.65	±0.1		9.23	
14291626XX	16	26/0.254	1.50	0.31	2.15	±0.1	15.06	15.38	610
14291601XX	16	1/1.29	1.29	0.31	1.95	±0.1		14.12	

备注：XX代表颜色，01黑色02白色03灰色04橙色05绿色06红色07蓝色08黄色09棕色10紫色11粉色；双色线用4位表示，前面部分为主色，例如白/黑，0201