



Brand	BOE	Model P/N	MV238FHM-N30
Diagonal Size	23.8"	Panel Type	a-Si TFT-LCD, LCM
Resolution	1920(RGB)×1080, FHD 92PPI	Pixel Format	RGB Vertical Stripe
Active Area	527.04(W)×296.46(H) mm	Bezel Opening	530.2(W)×299.6(H) mm
Outline Dim.	540.2(H)×315.6(V) ×14.2(D) mm	Treatment	Antiglare (Haze 25%), Hard coating (3H)
Luminance	250 cd/m ² (Typ.)	Contrast Ratio	1000:1 (Typ.) (TM)
View Direction	Symmetry	Response Time	14 (Typ.)(G to G)
Viewing Angle	89/89/89/89 (Typ.)(CR≥10)	Operating Mode	ADS, Normally Black, Transmissive
Support Color	16.7M 72% NTSC	Light Source	WLED [3 strings] , 30K hours , W/O Driver
Weight	2.24Kgs (Typ.)	Designed For	
Frame Rate	75Hz	Touch Panel	Without
Interface Type	LVDS (2 ch, 8-bit) , 30 pins Connector		
Power Supply	5.0V (Typ.)		
Environment	Operating Temperature: 0 ~ 50 °C ; Storage Temperature: -20 ~ 60 °C		

[★ Add to Favorites](#)[🔊 Book Stock Alert](#)[✚ Add to Compare](#)[🇺🇸 North American Sales](#)[🇯🇵 日本販売](#)