

INTRODUCTION



- The complete mechanical anti-theft lock is locked at the gearshift or at other relevant mechanisms. Has no interference to the circuits and oil passages, and with low breakdown.
- Harden steel materials of cylinders with anti-turning slice for anti-drilling, anti-sawing, anti-punching, anti-pickup.
- Exquisite and Hidden installation, doesn't occupy space and keyless. Spin-on security can lock up in 1 second easily and quickly.
- The cylinder is dual-H tumbler structure which contains 25 thousand types of combination. It is difficult to pickup even for a professional locksmiths.
- With computer ID system, keys can not be duplicated by ordinary lock shops.

INSTRUCTIONS

I. Pin-Lock Lock Unlock

1. Press the cylinder and turn left to the end
2. Lock
3. Insert the key
4. Turn it clockwise of 45 degrees
5. Unlock
6. Turn the key back then take out

II. Push-Lock Lock Unlock

1. Place the cylinder in
2. Lock
3. Insert the key
4. Turn it clockwise of 45 degrees
5. Take the cylinder out
6. Place the cylinder in the storage case

III. Rotary-Lock Lock Unlock

1. Unlock
2. Press the cylinder
3. Turn it counterclockwise of 120 degrees
4. Lock
5. Insert the key
6. Turn it clockwise of 120 degrees
7. Turn the key back then take out