








XIANGRUN	contact /tel.联系人/电话 :	mia +86 13539056172	
GUANGDONG,DONGGUAN,CHINA		mia@xiangrundg.com	
Product Model 产品型号	Picture 图片	Spec&Selling Points/规格&卖点	Cert./Test Report
XR-ODE1A2C33		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  4000W Power Rate</p> <p>Output:  AC OUTPUT 16A 250V, 4000W  DC OUTPUT USB-C1/C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A1 Total: 5V=3.6A, 18W</p>	tuv ce lvd erp rohs reach
XR-EDE1A2C33		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  4000W Power Rate</p> <p>1.5M, 3X1.5mm<sup>2</sup>  Output:  AC OUTPUT 16A 250V, 4000W  DC OUTPUT USB-C1+C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A Total: 5V=3.6A, 18W</p>	tuv ce lvd erp rohs reach
XR-OUK1A2C33		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  3250W Power Rate</p> <p>Output:  AC OUTPUT 13A 250V, 3250W  DC OUTPUT USB-C1/C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A1 Total: 5V=3.6A, 18W</p>	tuv ce lvd erp rohs reach
XR-EUK1A2C33		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  3250W Power Rate</p> <p>Output:  AC OUTPUT 13A 250V, 3250W  DC OUTPUT USB-C1/C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A1 Total: 5V=3.6A, 18W</p>	tuv ce lvd erp rohs reach

<p>XR-EBR1A2C33</p>		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  3250W Power Rate</p> <p>Output:  AC OUTPUT 10A 250V, 2500W  DC OUTPUT USB-C1/C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A1 Total: 5V=3.6A, 18W</p>	
<p>XR-OFR1A2C33</p>		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  4000W Power Rate</p> <p>Output:  AC OUTPUT 16A 250V, 4000W  DC OUTPUT USB-C1/C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A1 Total: 5V=3.6A, 18W</p>	<p>tuv ce lvd erp rohs reach</p>
<p>XR-EFR1A2C33</p>		<p>USB 2C1A GaN 33W  ANTI SURGE NTC  Lightning Protection MOV 2500V  Shell material:  PC 94V-0 fire retardant,  Metal Material:Plating Phosphor bronze  16A Overload Protector  1 X 3PIN AC Outlet  2 X 2PIN AC Outlet  4000W Power Rate</p> <p>1.5M, 3X1.5mm<sup>2</sup></p> <p>Output:  AC OUTPUT 16A 250V, 4000W  DC OUTPUT USB-C1+C2+USB-A  PDO 5V=3.0A, 9V=3.0A, 12V=2.5A,  15V=2.0A, 20V=1.5A, 30W  PPS: 3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W  QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A,  20V=1.5A, 30W  C1+C2+A Total: 5V=3.6A, 18W</p>	<p>tuv ce lvd erp rohs reach</p>