



深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co., Limited

Add: 2505 Sogbai Road, Shiyan Town, Baoan District, Shenzhen, China
Contact Person: Ms Helen Qin Skype: helenqin32 Mob/WhatsApp/ Wechat: +86 17688933149
Email: sales02@szxgled.com
Web: www.xgled.com

P3 indoor led display parameter.

LED Module	
	pixel pitch
	3mm
	module size
	192*192mm
	module resolution
	64*32dots
	LED
	SMD2121
Scan	
1/32scan	
Application	
indoor	
Weight	
0.3KG	
Chip type	
Epistar	

LED Cabinet	
	Cabinet Size
	576mm(W)768mm(H) (Color can be chosen)
	Cabinet resolution
	192*256dots
	module quantity
	3*4pcs
LED driver brand	
Youyi	
Material	
Iron	
Receiving card	
1pcs	

LED Screen				
	Pixel	111111dots/m²	Continuous Working Hours	>72 hours
	Ave power consumption	280W/m²	Using Life	100,000 hours
	Max power consumption	800W/m²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥3m	Scatter OOC Point	<0.01%
	Brightness(cd/m²)	≥1200cd	Continuous OOC Point	None
	Refresh Rate	1920 frame/s	IP Grade	IP40/IP30
	LED Drive mode	Constant Current	Working Temperature	-35C----+60C
	Display color	17M——69G	Working Humidity	1---70%
	Viewing angle	W140° ,H140°		



深圳市星光彩科技有限公司 Shenzhen Xing Guang Cai Technology Co., Limited

4.Regular packing:



5.Certifications: CE ROS FCC CCC

