

Shengzhen Kingt Technology Co.,Ltd.

	
Model Type:	KGT-4318 (A2+)
Name of Commodity:	Flatbed Printer(universal printer)

Specification :

Print Method	Non-contact inkjet printing
Technology	Advanced Micro Piezoelectric printing technology
Resolution	2880*1440dpi
Print direction	Automatic single / bidirectional printing
Nozzle deploys	Technology 1440 nozzles (180 nozzles*8 color)
ink droplet size	1.5 pico-liter

Print speed:

A2+	About 5 munites (print full size in 2880dpi)
-----	--

Ink deploys:

Solvent Ink / ECO-Solvent Ink	Y(T0544)Yellow
	M(T0543)Magenta
	C(T0542)Cyan
	LM(T5816)Light carmine
	LC(T5815)Light cyan
	MK(T0548)Matter black
	PK(T0541)Photo Black
	LLK(T5819)Light light black

Ink Supply System : Low Ink Detector, Auto or Manual Ink Supply System

Print specification & size:

Maximal print area	43*75 CM
Printing thickness	Within 17 CM
Printhead Height	2 to 6 mm Above Media (Adjustable)

Operational enviroments:

Temperature	10 ~ 35 degrees
Humidity	20~80%RH

Enviroment	Little Dust workshop
Wind power around	not too much.

Electric specification:

Input Power	AC220V~240V/AC110V~120V
Rated Frequency	50HZ~60HZ
Power consumption	Runtime 35W

Control system:

up-down system	Stepper motor + Screw with Italy belt
Feeding system	Servo motor with timing belt (3GT Italy)
Media height check	Infrared intelligent scanning
Control mode	Intelligent Germany touch screen
Nozzle Protection	Infrared detection of automatic adjustment
Language	switch in Chinese and English

Data transmission:

Printing connector	USB2.0 (high speed)/ IEEE1394
Input buffer	65M
Transmission speed	400MBPS

Equipment size:

Machine size	115*74*55cm
Package size	125*85*85cm
net weight	75KG
gross weight	100KG

Machine accessories:

Printer Driver CD	EPSONR1800 Drive
Product instruction	The operation guide/ trouble removal waits
operating software	Adobe Photoshop CS3, Illustrator, etc.
USB2.0/3M / Transparent Blue	A bar
power supply cable manual	A bar
ECO-Solvent Ink	9*150 ML (Y , M , C , LM , LC , LK , LLK , PK, MK)
Special Coating	One bottle
Accessories	injector 50ML(2 pcs)+5ML(2 pcs)+20ML(7 pcs)
	Cleaning liquid+Moisture Fluid+Sensor(2 pcs)
Warranty : 1 year aftersale service and life-long technical support	