

ABS Key fobs - Product Spec. (ver. 2.1)



IC	EM42000 / TK4100	TEMIC (T5577)	MIFARE Ultralight®	MIFARE Classic® 1K	MIFARE Classic® 4K	TI Tag-it	ICODE SLI
Memory	64 bits	330 bits	512 bits	1 K bytes	4 K bytes	2K bits	1024 bits
Frequency	125 KHz		13.56 MHz				
Function	Read only		Read / Write				
Dimensions	AB0000	36.9 x 30.5 x 7.7 mm		AB0010	35.0 x 23.0 x 3.9 mm		
	AB0001	43.7 x 30.5 x 5.3 mm		AB0016	53.9 x 33.8 x 5.0 mm		
	AB0003	40.5 x 32.0 x 4.2 mm		AB0020	50.0 x 31.0 x 6.5 mm		
	AB0005	53.0 x 37.5 x 9.8 mm		AB0021	40.0 x 31.0 x 6.5 mm		
	AB0006	52.5 x 35.2 x 9.0 mm					

Material	Weight	Surface	Operation Temperature	Storage Temperature
ABS	4.2 ~ 10 g	Matte	0°C ~ 55°C	-25°C ~ 75°C

- MIFARE and MIFARE Classic are registered trademark of NXP B.V. and are used under license.
- MIFARE and MIFARE Ultralight are registered trademark of NXP B.V. and are used under license.