

ADI-F4F-003

720P HD XVI/AHD Analog Camera

Features:

- 720P HD resolution, the image is more clear and delicate;
- Zero-latency data transmission, full real-time, high fidelity;
- Long transmission distance, coaxial transmission up to 500 meters;
- Support UTC, not support OSD by the back-end;
- Support coaxial upgrade, version upgrade convenient and efficient;
- Compatible with AHD/TVI/CVI back-end;
- Support XVI/AHD/TVI/CVI/CVBS DVR;
- NTSC&PAL 2 in 1, easy to switch through back-end;
- High-definition quality products with competitive price;

**Parameters:**

Model	ADI-F4F-003
ISP	XM310V300
Sensor	1/4.0 inch SP140A sensor
Signal format	XVI/AHD/TVI/CVI
Video Resolution	PAL/NTSC : 1280×720
Minimum Illumination	Color:0.1Lux@(F1.2,AGC ON),0Lux with IR Black & White:0.01 Lux@(F1.2,AGC ON),0Lux with IR
Alarm Interface	can be connected with Passive Infrared Detection devices(PIR)
Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage
Shutter	1/50(1/60) seconds to 1/50,000 seconds
Lens	Built-in 1MP 2.8mm HD Lens(M12 Lens Mount)
IR LED	4pcs Array IR LED/4pcs Warm/White Light LED Optional(Full Color Night Vision)
IR Distance	IR Effective Distance 15Meters(Full Color Night Vision 15 Meters)
Day and night	Support IR-CUT
Noise reduction	Support 2D
WDR	No
UTC	Support UTC Coaxial Control Up to 500 Meters,Coaxial upgrade
OSD	No
Video output	XVI/AHD/TVI/CVI 720P@25FPS
Reliability	Comprehensive lightning protection, 7 * 24 hours -10℃~65℃high temperature stable and reliable testing
Material	ABS Plastic Housing
Application	Outdoor(Weatherproof IP66 Standard)
Working Temp.	- 10 ℃ ~ 60 ℃, humidity is less than 90% (no condensation)
Sync	2:1 interlace internal Sync.
Video Out	1.0Vp-p, 75Ω Composite, BNC x 1
Power	DC12V±10%
Power Consumption	≤8W
Package Dimension	9*10*10CM
Weight	0.5kgs

