

Foshan Xincode Electronics Technology Co., Ltd.

Attn:Janet Lee Email: xincode02@gmail.com MSN: xincode02@hotmail.com Skype: [xincode02](#)

X-660 Bluetooth Laser Barcode Scanner

Characteristics

- (1) Support Windows +Android+ IOS systems and suitable for Smartphones, Tablet PC, Laptops and Desktops.
- (2) Fully support connecting with any Bluetooth 2.0 device without using an external adapter.
- (3) Excellent power management solutions. The optical parts oscillate only when the scanner is in reading condition and that effectively extend the service life of the scanner.
- (4) The transmission power is only 1 mw which will not have radiation to the human body.
- (5) With infrared induction function (optional)
- (6) 750mA long lasting lithium battery inside
- (7) Have many scanning modes like continuous scanning, manual trigger, multiscan and auto switch off.
- (8) Built-in 64 KB memorizer can store about 3500 bar codes under inventory mode. (customizable)
- (9) Built-in 2 KB memorizer can store 110 bar codes in case Bluetooth connection interruption occurs.



Technical Parameters

Model No.	X-660
PHYSICAL CHARACTERISTICS	
Material	ABS+TPE+PC
Size	L*W*H:170mm*64mm*97mm
Color	White, Black
Power Supply	Built-in rechargeable 3.7V 750mA lithium battery
Accessories	Lithium battery, Charger, Bluetooth adapter
Weight	139g (With battery)
PERFORMANCE CHARACTIESTICS	
Radio Range	10m Visual range

Foshan Xincode Electronics Technology Co., Ltd.

Attn: **Janet Lee** Email: xincode02@gmail.com MSN: xincode02@hotmail.com Skype: **xincode02**

Module	Bluetooth class 2.0Version+EDR
Interface Supported	USB
Communicate Mode	SPP
Light Source(Laser)	Laser LED 650± 20nm (national class I laser safety standard)
Decode Capability	Codabar, Code 11,Code 93,MSI,Code128,UCC/EAN-128,Code 39,EAN-8,EAN-13,UPC-A,ISBN,Industrial 25,Standard 25,2/5 Matrix, etc.
Resolution	Min 0.1mm(4mils)
Depth of Field	3~9cm(0.1mm bar width);3.5~45cm(0.3mm bar width)
Decoding Speed	100 times/sec
Scan Width	5cm~30cm
Prompting Mode	Buzzer, Indicator light
Print Contrast	30%
Scan Angles	Roll 30°Pitch 75°Yaw65°
Cylinder Horizontal Scan	Diameter 35mm
USER ENVIRONMENT	
Operating Temp.	0 to 50°C / 32 to 122°F
Storage Temp.	0 to 50°C / 32 to 122°F
Operating Humidity	20~85% (non-condensing)
Storage Humidity	20~85% (non-condensing)
Shock Resistance	1.5m free fall on concrete surface

Pictures

