100W GaN power strip desktop charger with AC socket Specifications	
Model No.	P1710B
Input	
Input voltage range	90Vac - 264Vac
Normal voltage range	100Vac - 240Vac
Input frequency range	47Hz-63Hz
Rated input frequency	50Hz/60Hz
Max input AC	3A max at full load condition
Output	
US AC Socket	1100W :110V/10A
use 1 port	
USB-C1/C2	100W-PD:5V/3A.9V/3A.12V/3A.15V/3A.20V/5A PPS:3.3-21V/4.75A
USB-C3	65W-PD:5V/3A.9V/3A.12V/3A.15V/3A.20V/3.25A PPS:3.3-11V/5A
USB-A	QC18W:5V/3A.9V/2A.12V/1.5A
use 2 ports	
C1+C2/C3	C1-PD65W(5V/3A.9V/3A.12V/3A.15V/3A.20V/3.25A)+ C2/C3-PD35W(5V/3A.9V/3A.12V/2.5A.15V/2A.20V/1.75A) C1-PPS:3.3-11V/5A C2/C3-PPS:3.3-11V/3A
C1/C2+A	C1/C2-PD65W(5V/3A.9V/3A.12V/3A.15V/3A.20V/3.25A)+QC18W(5V/3A.9V/2A.12V/1.5A) C1/C2-PPS:3.3-11V/5A
C2+C3	C2-PD65W(5V/3A.9V/3A.12V/3A.15V/3A.20V/3.25A)+PD35W(5V/3A.9V/3A.12V/2.5A.15V/2A.20V/1.75A) C2-PPS:PPS:3.3-11V/5A C3-PPS:PPS:3.3-11V/3A
use 3 ports	
C1+C2+C3	C1-PD45W(5V/3A.9V/3A.12V/3A.15V/3A.20V/2.25A)+C2-PD35W(5V/3A.9V/3A.12V/2.5A.15V/2A.20V/1.75A)+C3-PD20W(5V/3A.9V/2.22A.12V/1.67A) C1_PPS:3.3-11V-5A C2-PPS:3.3-11V/3A C3-PPS:3.3-11V/2.2A
C1+C2+A	C1-PD45W(5V/3A.9V/3A.12V/3A.15V/3A.20V/2.25A)+C2-PD35W(5V/3A.9V/3A.12V/2.5A.15V/2A.20V/1.75A)+QC18W(5V/3A.9V/2A.12V/1.5A)
C1+C3+A	C1-PD65W(5V/3A.9V/3A.12V/3A.15V/3A.20V/3.25A)+C3-PD7.5W(5V/1.5A)+QC7.5W(5V1.5A)

Use full ports	
C1+C2+C3+A	C1-PD45W(5V/3A.9V/3A.12V/3A.15V/3A.20V/2.25A)+C2-PD35W(5V/3A.9V/3A.12V/2.5A.15V/2A.20V/1.75A)+C3-PD7.5W(5V/1.5A)+QC7.5W(5V/1.5A)
Charging Protocol & Intelligent Identification	Support PD3.0 or PD2.0 ,QC3.0/QC2.0,Support PPS,AFC,SCP,FCP,Support BC1.2
Output power	100W Max
Output Ripple	≤200
Physical specifications	
Color	Black
Shell Type	Plastic
Cable length	1 meter
Shell material	PC (Temperature resistance: 120℃) PC material meets the requirement of spherical pressure test.
LED Indicators	Indicate blue color when charging
Product size	100*100*25.2mm
Product weight	468g
Protection	
Over Load Protection	Short Circuit Protection
Over Current Protection	Over Temperature Protection
Environment Requirements	
Operating Temperature and Humidity	0℃ to 25℃ 10%RH to 90%RH
Storage Temperature	-20℃ to 80℃
Features	
●**2-in-1 Function**: The desktop 100W GaN charger with AC socket plays the role of both a charger and a power strip, allowing it to fast charge 4 devices and power up to 6 devices at a time in total.	
●**6-IN-1 fast charging station:**With dual US AC outlets, 2*USB-C PD output 100W, 1*USB-C PD output 65W and 1*USB-A QC 18W, this 6-in-1 Charging Station enables intelligently delivers power for up to 6 devices simultaneously. Designed to charge laptops ,tablet, and phones and other related devices at the same time, All-in-one design can meet your all daily works!	
●**100W High-power Fast Charging**, fast charge your MacBook Pro 16" M1 2021 from 0% to 33% in just 30 mins.	

• **GaN III Chip** that Conferred Higher Power and Better structural optimization, energy-efficient, compact size.
• **With Multiple security protections** of overLoad Protection,overcurrent protection and short circuit protection,Over Temperature Protection,you and your electronic devices and appliances are completely protected!