

K7026-3T-1 三刀头单工位线上孔料机

产品详情：（中文）

应用范围：针对人造石、石英石、大理石、黄岗岩台面加工行业开发的高性能自动流水线开孔、切角设备。

设备功能：台面灶孔、台上盆、台中盆、台下盆、后墙包柱缺角切割、斜接接驳口切割。

基础加工：设备采用整体钢管焊接，退火处理，加工母机为日本马扎克五轴数控龙门铣床，有效保证了设备的使用寿命和加工精度。

配置选用：核心机械及电器件全部采用进口或国内一线品牌，有效保证了设备的运行稳定性和质量。

傻瓜式操作：控制系统为自有软件部独立开发，设备可达到傻瓜式操作，有效避免了从业人员素质偏低造成的入行门槛高的问题。流水线自动进出料自动加工设计极大得符合了台面行业现在的发展趋势，有效降低了工厂的加工粉尘，提高了产品标准化，所用操作工无差异化要求。

加工质量保证：此款设备采用三刀头自动切换、线上加工的设计方式，操作简单，加工效率高，完成质量好。

本是标准化台面加工厂的首要选择！

（英文）

K7026-3T-1 Quartz Sink Hole Cutting Machine

Scope of application: High-performance automatic assembly line opening and chamfering equipment developed for artificial stone, quartz stone, marble and countertop processing industry.

Equipment functions: table top stove hole, above counter basin, Taichung basin, under counter basin, back wall pack with missing corner cut, and oblique joint joint cut.

Basic processing: The equipment is welded and annealed by integral steel pipe. The machining machine is a Japanese Mazak five-axis CNC gantry milling machine, which effectively guarantees the service life and machining accuracy of the equipment.

Configuration selection: The core mechanical and electrical components are all imported or domestic first-line brands, which effectively guarantees the operational stability and quality of the equipment.

Fool-type operation: The control system is independently developed by own software department, and the equipment can reach the fool-like operation, effectively avoiding the problem of high entry threshold caused by the low quality of the practitioners. The automatic processing of automatic feeding and discharging of the assembly line has greatly met the current development trend of the countertop industry, effectively reducing the processing dust of the factory, improving the standardization of the products, and the requirements for the operators to be used without differentiation.

Processing quality assurance: This equipment adopts three-knife automatic switching and on-line processing design, which is easy to operate, high in processing efficiency and good in quality.

This machine is the primary choice for standardized countertop processing plants!

技术参数:

三刀头单工位线上孔料机		
型号	unit	K7026-3T-1
外形宽度	MM	2100
外形长度	MM	4500
外形高度	MM	1800
可加工板材尺寸宽度	MM	550-700
可加工板材尺寸长度	MM	600-2600
可加工板材尺寸高度	MM	12-20
加工速度参数	MM/MIN	1000-12000
用电总功率参数	KW	12
工作电压参数	V	AC380
电动机	/	定制 7.5KW 电主轴
电机转速	RPM/MIN	24000
控制系统	/	KL 专业版
换刀类型	/	三头气动换刀