



HC-35



产品种类: 热镀锌铁丝、电镀锌丝

标准尺寸: BWG8-BWG36

T/S(千克/毫米²): 30-55

包装: 每卷重1-500千克; 内塑料膜外编织袋或麻布。

The varieties of products: Hot dipped galvanized wire, electro-galvanized iron wire

The standard size: BWG8-BWG36

T/S(kg/mm²): 30-55

Packing: 1-500kg/coil, PVC film inside, plastic bag or hessian cloth outside.

HC-36



产品种类: 黑色退火铁丝、软亮退火铁丝

标准尺寸: BWG5-BWG39

T/S(千克/毫米²): 30-55

包装: 每卷重1-500千克; 内塑料膜外编织袋或麻布。

The varieties of products: Black annealed iron wire, soft light annealed iron wire

The standard size: BWG5-BWG39

T/S(kg/mm²): 30-55

Package: 1-500kg/coil, lined with PVC strips and wrapped with plastic bag or hessian cloth.

HC-37



产品种类: 涂塑铁丝

PVC涂层: 最低涂层0.4mm

T/S(千克/毫米²): 30-55

颜色: 绿、兰、黄、桔黄、灰及其它

包装: 内塑料膜外编织袋或麻布。

The varieties of products: PVC coated wire

PVC Coating: The lowest coating 0.4mm

T/S(kg/mm²): 30-55

Color: Green, blue, yellow, orange, gray and so on

Package: Lined with PVC strips and wrapped with plastic bag or hessian cloth.

HC-38



截断丝/ Cutting Wire

丝径: 0.7mm-5.0mm

规格: 20cm-200cm

Wire diameter: 0.7mm-5.0mm

Specification: 20cm-200cm

C型钉

C Ring Staple

材质: 低碳钢、高镀锌层

抗拉强度: 35-45kg

丝径: 1.6mm=16gauge

包装数量: 26000支/箱

Technical information material:

Low-carbon, high zinc-plated layer

Tensile strength: 35-45kg

Line diameter: 1.6mm=16Gauge

Packing: 26000 sticks/box

HC-39



U型丝/ U Tie Wire

规格: 直径2.0mm ~ 5.0mm 长度250mm ~ 3000mm

直径0.7mm ~ 1.2mm 长度250mm ~ 750mm

种类: 黑U型丝、镀锌U型丝

包装: 根据客户要求生产



Production Range:

Dia: 2.0mm-5.0mm Length: 250mm-3000mm

Dia: 0.7mm-1.2mm Length: 250mm-750mm

Surface: Black U Tie Wire and Gal. U Tie Wire

Packing: According customer's request

HC-41

