

FEATURES:

- * 3 microphone input, 3 Aux input, and one Aux output for link
- * Transformer isolated 100V, 70V and 4 Ω speaker output
- * Muting function
- * Individual volume control
- * Low and high tone control
- * A five-element LED level meter is provided for quick and easy visual monitoring of the sound level
- * Short circuit protection & alarm
- * Chime out prior to other inputs
- * Individual distributor for 6 channels
- * 24V DC backup sources

	MA-8120	MA-8240	MA-8360	MA-8480	MA-8560	MA-8630
Main supply	220-240V/50Hz					
Power consumption	240W	480W	720W	960W	1120W	1300W
Output	120W	240W	360W	480W	560W	650W
Output Regulation	< 3dB					
Frequency response	100Hz-16000Hz					
Distortion(THD)	<0.3% at 1KHz, 1/3 rated power output					
Speaker outputs	4-16 Ω , 70V, 100V					
Aux output	600 Ω , 1V (0dB)					
Input	Mic 1, 2, 3: 600 Ω , 6mV unbalanced; Aux1, 2, 3: 10K Ω , 250mV, unbalanced					
S/N ratio	Mic 1, 2, 3: $\geq$ 66dB; Aux1, 2: $\geq$ 70dB					
Tone control	Bass: $\pm$ 10dB at 100Hz; Treble: $\pm$ 10dB at 10KHz					
Protection	AC Fuse, DC Voltage, Overload and short circuit					
Backup	24V DC					
Muting function	0-30dB					
Dimensions(WxHxD)	440x92x330mm				440x92x410mm	
Net weight	12kg	14.5kg	15kg	20kg	21kg	24kg