

Item	Model / Picture	Discription
1	 AN-A60-5W	Power 5w, Input220-240V, PF>0.9, 6500K, CRI>70, Package: 62x32x24cm/100pcs, GW: 4.7kg, PCB size/thickness: 45.8mm/0.63mm, light size: D60x110mm, LPW: 50lm/w, Material: plastic-clad aluminum
2	AN-A60-7W	Power 7w, Input220-240V, PF>0.9, 6500K, CRI>70, Package: 62x32x24cm/100pcs, GW: 4.7kg, PCB size/thickness: 45.8mm/0.63mm, light size: D60x110mm, LPW: 50lm/w, Material: plastic-clad aluminum
3	AN-A60-9W	Power 9w, Input220-240V, PF>0.9, 6500K, CRI>70, Package: 62x32x24cm/100pcs, GW: 4.7kg, PCB size/thickness: 45.8mm/0.63mm, light size: D60x110mm, LPW: 50lm/w, Material: plastic-clad aluminum
4	AN-A60-12W	Power 12w, Input220-240V, PF>0.9, 6500K, CRI>70, Package: 62x32x24cm/100pcs, GW: 4.7kg, PCB size/thickness: 45.8mm/0.63mm, light size: D60x118mm, LPW: 50lm/w, Material: plastic-clad aluminum
5	AN-A65-12W	Power 12w, Input220-240V, PF>0.9, 6500K, CRI>70, Package: 68x32x24cm/100pcs, GW: 4.7kg, PCB size/thickness: 45.8mm/0.63mm, light size: D65x122mm, LPW: 50lm/w, Material: plastic-clad aluminum